

CPF 11 – Cabine Protection Foil 60cm x 100m

General description

A high tack masking film for use in interior and exterior applications. The product consists of a self wound, low density polyethylene film with ultraviolet inhibitor and is coated with a custom formulated water based acrylic adhesive.

Physical specifications	
Nominal Thickness	76 µm
Type adhesive	Water based acrylic adhesive
Adhesion range	90 – 157 g/cm
Tensile strength	MD 245 kg/cm ² TD 203 kg/cm ²
Elongation	MD 450% TD 750%

Recommended uses

Ideal for the masking and protection of matte anodized and mill finish aluminium. Excellent performance on matte and textured painted metals, and matte and textured high pressure laminates. Adequate performance nameplate substrates such as textured PET and polycarbonate.

Shelf life

12 months from purchase

This information corresponds to our current knowledge on the subject. It is offered solely to provide possible suggestions for our own experimentation.

It is not intended, however, to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes.

This information may be subject to revision as new knowledge and experience becomes available.

Since we cannot anticipate all variations in actual end-use conditions, Chemicar make no warranties and assume no liability in connection with any use of this information.

This information does not constitute a specification and is only intended to show the typical properties of the product. Product safety information is available on request.

Data in this Technical Data Sheet relates only to the specific materials designated here in and not to use in combination with any other material or process.

The information given here is the best available at time of issue. It is based on our present knowledge but does not constitute a contractual description of product properties.