



# TDS

## TECHNICAL DATA SHEET

### TECHNICAL SHEET

### PLA 03 – Finixa HDPE masking film static in a box-green

#### Product data

Density:	0,952 g / cm <sup>3</sup>
Thickness:	8 µm
Tensile Strength <i>machine direction</i> :	≥ 50 N / mm <sup>2</sup>
Tensile Strength <i>transverse direction</i> :	≥ 16 N / mm <sup>2</sup>
Elongation at break <i>machine direction</i> :	> 365 %
Elongation at break <i>transverse direction</i> :	> 540
Dart drop:	≥ 6 g/µm
Dimension and design:	as ordered

#### Indications for storage and application

Storage time:	12 months from delivery date
Storage temperature:	+ 20°C / ± 10°C
Relative humidity (RH):	30-90%
Storage:	in closed rooms
Exposure to UV-radiation:	to avoid; *not applicable for UV-resistant film

DIMENSION:	380cm x 200m 32 rolls on a pallet
------------	--------------------------------------

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the product's suitability for their own applications.*