

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Finixa spray anti-gravel grey 400ml  
Product code : TSP 210  
Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use  
Use of the substance/mixture : Non industrial spraying  
Industrial spraying  
Function or use category : Coatings and paints, thinners, paint removers

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Chemicar Europe NV  
Baarbeek 2  
2070 Zwijndrecht  
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89  
[info@chemicar.eu](mailto:info@chemicar.eu)

#### 1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazardous ingredients :

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics;  
Reaction mass of ethylbenzene and xylene;  
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane;  
butane

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H304 - May be fatal if swallowed and enters airways.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H412 - Harmful to aquatic life with long lasting effects.

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, eye protection.  
P301+P310 - IF SWALLOWED: Immediately call a doctor.  
P331 - Do not induce vomiting  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403 - Store in a well-ventilated place.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

### Scandinavian countries regulation

Denmark

MAL code

: 5-3

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5	10 - 25	Flam. Gas 1, H220 Press. Gas
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	(CAS-No.) 68920-06-9 (EC-No.) 920-750-0	10 - 25	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butanone; ethyl methyl ketone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0	2.5 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	(EC-No.) 926-605-8	2.5 - 10	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
1-methoxy-2-propanol; monopropylene glycol methyl ether	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3	2.5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
butane	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0	2.5 - 10	Flam. Gas 1, H220 Press. Gas
isobutane (containing ≥ 0,1% butadiene (203-450-8))	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (EC Index-No.) 601-004-01-8	1 - 2.5	Flam. Gas 1, H220 Press. Gas Carc. 1A, H350 Muta. 1B, H340

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

HYDROGENATED TALLOWALKONIUM CHLORIDE	(CAS-No.) 61789-72-8 (EC-No.) 263-081-3	0.25 - 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400
ethanol; ethyl alcohol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	0.1 - 1	Flam. Liq. 2, H225

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: No irritant effect.
First-aid measures after eye contact	: In case of contact, immediately rinse eyes with plenty of water for at least 15 minutes. Consult an ophthalmologist if irritation persists. Rinse opened eye for several minutes under running water. Then consult doctor.
First-aid measures after ingestion	: Do not induce vomiting. Immediately call a POISON CENTER/doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Alcohol resistant foam. extinguishing powder. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Protection during firefighting	: Approved respirator.
--------------------------------	------------------------

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable protective clothing.
------------------	--------------------------------------

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
----------------------	---

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Do not discharge into drains or rivers. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Provide adequate ventilation.
Methods for cleaning up	: Do not flush with water.

#### 6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Ensure adequate air ventilation.
Precautions for safe handling	: Handle and open container with care. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Do not spray on an open flame or other ignition source.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep dry.
Special rules on packaging	: Container should not be closed gas-tight. Store in a closed container.

#### 7.3. Specific end use(s)

No additional information available

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### ethanol; ethyl alcohol (64-17-5)

##### Belgium - Occupational Exposure Limits

Local name	Alcool éthylique # Ethanol
Limit value (mg/m <sup>3</sup> )	1907 mg/m <sup>3</sup>
Limit value (ppm)	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018

##### 74-98-6 Propane

WEL	Long-term value: 1800 mg/m <sup>3</sup>
-----	---

##### 74-98-6 Butanone

WEL	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm Sk, BMGV
-----	---

##### 107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm Sk
-----	---

##### 106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

##### 75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8))

WEL	Short-term value: 2400 mg/m <sup>3</sup> Long-term value: 1900 mg/m <sup>3</sup>
WEL	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm

##### DNELs

##### 68920-06-9 Hydrocarbons, C7-C9, n-alkanes, isoalkanes,cyclics

Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
		773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m <sup>3</sup> (Consumer)
		2035 mg/m <sup>3</sup> (Worker)

##### 78-93-3 butanone

Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
		1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m <sup>3</sup> (Consumer)
		600 mg/m <sup>3</sup> (Worker)

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reaction mass of ethylbenzene and xylene		
Oral	DNEL Long term-systemic	1.6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer)
		180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	289 mg/m3 (Worker)
	DNEL Long term-systemic	14.8 mg/m3 (Consumer)
		77 mg/m3 (Worker)
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes		
Oral	DNEL Long term-systemic	1301 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	1377 mg/kg bw/day (Consumer)
Inhalative	DNEL Long term-systemic	1131 mg/m3 (Consumer)
		5306 mg/m3 (Worker)
107-98-2 1-methoxy-2-propanol		
Oral	DNEL Long term-systemic	3.3 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	18.1 mg/kg bw/day (Consumer)
		50.6 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	553.5 mg/m3 (Worker)
	DNEL Long term-systemic	43.9 mg/m3 (Consumer)
		369 mg/m3 (Worker)
PNECs		
Reaction mass of ethylbenzene and xylene		
PNEC Freshwater	0.327 mg/l (Undefined)	
PNEC Marine water	0.327 mg/l (Undefined)	
PNEC Freshwater sediment	12.46 mg/l(dry weight) (Undefined)	
PNEC Soil	2.31 (Undefined)	
PNEC Sewage Treatment Plant	6.58 mg/l (Undefined)	
PNEC Marine water sediment	12.46 mg/l(dry weight) (Undefined)	
107-98-2 1-methoxy-2-propanol		
PNEC Freshwater	10 mg/l (Undefined)	
PNEC Freshwater sediment	41.6 mg/l(dry weight) (Undefined)	
PNEC Soil	2.47 (Undefined)	
Ingredients with biological limit values		
78-93-3 butanone		
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one	

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Additional Occupational Exposure Limit Values for possible hazards during processing:

#### 110-54-3 n-hexane

WEL Long-term value: 72 mg/m<sup>3</sup>, 20 ppm

### 8.2. Exposure controls

#### Appropriate engineering controls:

Wash hands before breaks and after work. Do not breathe gas/vapour/aerosol.

#### Personal protective equipment:

Gloves. Protective goggles.

#### Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Nitrile rubber gloves	Nitrile rubber (NBR)	5 (> 240 minutes)	>= 0.5		EN ISO 374

#### Eye protection:

Wear closed safety glasses. EN 166

#### Skin and body protection:

Wear suitable protective clothing

Type	Standard
	EN 13034

#### Respiratory protection:

Wear appropriate mask

Device	Filter type	Condition	Standard
Gas filters	Filter AX (brown), Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust	Short term exposure	
Self-contained breathing apparatus (SCBA)	Filter AX (brown), Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust	Long term exposure	
	Type A - High-boiling (>65 °C) organic compounds, Type P2	In the event of insufficient ventilation:	

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Colour	: Grey.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -44.5 °C
Flash point	: -97 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Vapour pressure	: 4900 hPa 20°C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.79 g/cm <sup>3</sup> 20°C
Solubility	: Practically not miscible. Organic solvent:68.9%
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.7 vol %
Upper explosive limit (UEL)	: 20 vol %

### 9.2. Other information

VOC content : 544.2 g/l VOC-CH: 68.89 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

### LD/LC50 values relevant for classification

#### Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes

Oral	DNEL Long term-systemic	1301 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	1377 mg/kg bw/day (Consumer)
Inhalative	DNEL Long term-systemic	1131 mg/m <sup>3</sup> (Consumer)

#### 78-93-3 butanone

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
		5000 mg/kg (rbt)

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reaction mass of ethylbenzene and xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes		
Oral	LD50	16750 mg/kg (rat)
Dermal	LD50	3350 mg/kg (rat)
Inhalative	LC50/4h	259354 mg/l (rat)
107-98-2 1-methoxy-2-propanol		
Oral	LD50	4016 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/6h	27596 mg/m3 (rat)
Finixa spray anti-gravel grey 400ml		
Vaporizer	Aerosol	

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

### Aquatic toxicity

#### 68920-06-9 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

NOELR (72h)	10 mg/l (Pseudokirchneriella subcapitata)
EL 50 (72h)	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>13.4 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)
EC50/48h	3 mg/l (Daphnia magna)

#### 78-93-3 butanone

LC50/96h	2993 mg/l (Pimephales promelas)
EC50/48h	308 mg/l (Daphnia magna)

#### Reaction mass of ethylbenzene and xylene

NOEC	1.3 mg/l (Fish)
NOEC (7 day)	0.96 mg/l (Daphnia magna)
NOEC (72h)	0.44 mg/l (algae)
NOEC (28 d)	16 mg/l (Bacteria)
LC50/96h	8.9-16.4 mg/l (Pimephales promelas)
EC50/48h	3.2-9.5 mg/l (Daphnia magna)



# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes	
NOELR (21d)	3.818 mg/l (Daphnia magna)
NOELR (28d)	2.187 mg/l (Oncorhynchus mykiss)
EL50(48h)	17.06 mg/l (Daphnia magna)
LL50 (96h)	9.776 mg/l (Oncorhynchus mykiss)
107-98-2 1-methoxy-2-propanol	
LC50/96h	6812 mg/l (Fish)
EC50/48h	23300 mg/l (Daphnia magna)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)

: Disposal must be done according to official regulations. Do not dispose of with domestic waste. Do not discharge into drains.

Product/Packaging disposal recommendations

: Disposal must be done according to official regulations.

HP Code

: HP3 - "Flammable:"

— flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;

— flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;

— flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;

— flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;





— water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;

— other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
UN 1950 , 2.1, (D)	UN 1950 , 2.1	UN 1950 , 2.1	UN 1950 , 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.4. Packing group

Not applicable

Not applicable

Not applicable

Not applicable

### 14.5. Environmental hazards

Dangerous for the environment :  
No

Dangerous for the environment :  
No  
Marine pollutant : No

Dangerous for the environment :  
No

Dangerous for the environment :  
No

No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 5F  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E0  
Tunnel restriction code (ADR) : D

#### Transport by sea

Limited quantities (IMDG) : 1 L  
Excepted quantities (IMDG) : E0  
EmS-No. (Fire) : F-D  
EmS-No. (Spillage) : S-U  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

#### Air transport

No data available

#### Inland waterway transport

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 544.2 g/l  
VOC-CH: 68.89 %

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WGK) 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

Waterbezwaarlijkheid : 1 - Black list substance

Saneringsinspanningen : A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken

SZW-lijst van kankerverwekkende stoffen : HYDROGENATED TALLOWALKONIUM CHLORIDE, ethanol; ethyl alcohol are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : ethanol; ethyl alcohol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : ethanol; ethyl alcohol is listed

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NIET-limitatieve lijst van voor de voortplanting : ethanol; ethyl alcohol is listed  
giftige stoffen – Ontwikkeling

### Denmark

Class for fire hazard : Class I-1  
Store unit : 1 liter  
Classification remarks : F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed  
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

# Finixa spray anti-gravel grey 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*