

TECHNICAL SHEET

TMF 81 – Rim masking film 80p. in dispenserbox

DESCRIPTION:

TMF 81 rim masking film is the most cost-efficient way to mask an alloy wheel for spot repair or repaint job, painting can be done without disassembling the tyre, this implies no recalibration need to be done after repair. Can be used on wheels from 15" up to 22/23", the Corona treatment ensure adhesion of overspray to get a perfect finish.

SPECIFICATIONS:

- Size foil:	145 x 145cm
- Thickness :	20mu
- Material:	HDPE tire cover with elastic cord
- Elongation elastic cord:	15" up to 22/23"
- Temperature resistance:	80°C
- Treatment:	Corona-treated for good paint absorption
- Maximum inner diameter:	580 mm
- Color:	Green with print
- Box	Include 4packs x 20pcs (color box (38*24*20cm))
- Individual Pack:	20pcs
- Quantity Pallet:	48boxes

APPLICATION:

- Deflate the tyre
- Makes sure the wheel is clean (grease, dirt and dust free)
- Break the tyre of the bead
- Push the tyre down
- Apply the TMF 81 around the alloy rim with the elastic band.
- Let go of the tyre to position the foil.
- Apply the paint
- After curing push down the tyre
- Remove the foil
- Inflate the tyre.

STORAGE AND SHELF LIFE:

Storage temperature: 20°C / +/-10°C

Relative humidity: 30 – 90%.

Storage: In closed rooms.

Exposure to UV-radiation: To avoid

Shelflife: 2 years, when storage instructions are respected.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.