

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : Finixa anti-gravel coating paintable grey - 1I
 Product code : AGG 01
 Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

1.2.2. Uses advised against

Restrictions on use : Non industrial spraying, Industrial spraying

1.3. Details of the supplier of the safety data sheet

Chemicar Europe NV
 Baarbeek 2
 2070 Zwijndrecht
 T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemicar.eu

1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
 Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
 Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.
 H336 - May cause drowsiness or dizziness.
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.
 P102 - Keep out of reach of children.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 - Do not breathe dusts or mists.
 P280 - Wear protective gloves, eye protection.
 P242 - Use non-sparking tools.
 P273 - Avoid release to the environment.
 P243 - Take action to prevent static discharges.
 P271 - Use only outdoors or in a well-ventilated area.
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Finixa anti-gravel coating paintable grey - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

Scandinavian countries regulation

Denmark

MAL code : 5-3

2.3. Other hazards

PBT: not relevant – no registration required
vPvB: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	(EC-No.) 920-750-0	25 - 50	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	2.5 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
ethanol; ethyl alcohol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	0.1 - 1	Flam. Liq. 2, H225

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Assure fresh air breathing. Get medical advice/attention if you feel unwell.
First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open.
First-aid measures after ingestion : Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO₂), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting : Full face piece respirator.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Complete protective clothing.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Finixa anti-gravel coating paintable grey - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Keep public away.

6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Keep public away.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ensure adequate air ventilation. Do not flush with water.

6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Avoid formation of vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry place. Store in a closed container. Keep cool.
Storage area : Store away from heat. Store in a well-ventilated place.
Special rules on packaging : Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m ³)	221 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	442 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Xylène, isomères mixtes, purs # Xyleen, mengsel van isomeren, zuiver
Belgium	Limit value (mg/m ³)	221 mg/m ³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m ³)	442 mg/m ³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
ethanol; ethyl alcohol (64-17-5)		
Belgium	Local name	Alcool éthylique # Ethanol
Belgium	Limit value (mg/m ³)	1907 mg/m ³
Belgium	Limit value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002

Finixa anti-gravel coating paintable grey - 1l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2. Exposure controls

Personal protective equipment:

Gas mask with filter type A. Gas mask with filter type AX at conc. in air >. Gloves. Protective goggles. EN 166. Protective clothing.

Hand protection:

Nitrile rubber gloves

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Grey.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 98 °C
Flash point	: 2 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 30 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.05 g/cm ³
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: 30 mm ² /s
Viscosity, dynamic	: 8000 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.7 vol %
Upper explosive limit (UEL)	: 7 vol %

9.2. Other information

VOC content	: 533.4 g/l
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

Finixa anti-gravel coating paintable grey - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Finixa anti-gravel coating paintable grey - 1I

Viscosity, kinematic	30 mm ² /s
----------------------	-----------------------

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Finixa anti-gravel coating paintable grey - 1I

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Disposal must be done according to official regulations.

European List of Waste (LoW) code : 08 02 99 - wastes not otherwise specified
20 01 27* - paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
14.1. UN number		
1139	1139	1139
14.2. UN proper shipping name		
COATING SOLUTION	COATING SOLUTION	Coating solution
Transport document description		
UN 1139 COATING SOLUTION (), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1139 COATING SOLUTION, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1139 Coating solution, 3, II, ENVIRONMENTALLY HAZARDOUS

Finixa anti-gravel coating paintable grey - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
III	II	II
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available		

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 640E
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:

Tunnel restriction code (ADR) : D/E

- Transport by sea

Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

- Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364

Finixa anti-gravel coating paintable grey - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

VOC content : 533.4 g/l

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 2, significant hazard to water (Classification according to AwSV, Annex 1)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

Waterbevaarlijkheid : 1 - Black list substance
Saneringsinspanningen : A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken
SZW-lijst van kankerverwekkende stoffen : ethanol; ethyl alcohol is listed
SZW-lijst van mutagene stoffen : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : ethanol; ethyl alcohol is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : ethanol; ethyl alcohol is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : xylene, ethanol; ethyl alcohol are listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
-----------------------	-------------------------------------

Finixa anti-gravel coating paintable grey - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product