

### MST 719-750 – Finixa masking tape 120° 19mm x 50m 48p.

#### Description

Waterproof green masking tape. silicone-free

#### Product data

Backing:	63 g/m <sup>2</sup> waterproof green saturated crepe paper
Adhesive:	dry natural rubber based
Total thickness	0.130mm
Adhesion to steel	4.8 N/25mm
Tensile strength MD	90 N/25mm
Elongation at break	8 %
Temp. Resistance	120 °C (30 min)

#### Application

Waterproof masking tape widely used for car repair applications as well as for wall-painting on building and construction sites and industrial use.

Features	Benefits
Dry natural rubber solvent based adhesive	<ul style="list-style-type: none"> <li>• Good adhesion on uneven surfaces also</li> <li>• Heat resistant up to 120°C ( 30 minutes )</li> <li>• Easy removal without adhesive residue, if it is removed as paint is dry.</li> </ul>
Water resistant saturated paper backing	<ul style="list-style-type: none"> <li>• Well conformable to most shaped surfaces</li> <li>• Highly resistant to moisture and water</li> <li>• Compatible with most common paints and lacquers</li> <li>• Removable without breaking</li> <li>• Hand tearable</li> </ul>

#### Product shelf life and storage

12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*