

TECHNICAL DATA SHEET

PRF 600 - Finixa self-adhesive protection film white 60 cm x 25m **PRF 1200 - Finixa self-adhesive protection film white 120 cm x 25m**

1. Product description

A white polypropylene film with a high tack acrylic adhesive, designed to protect any kind of surface (e.g. mixing tables, cabin floors) from chemical products (overspray, paint spills, oil, grease, ...).

2. Product features

- Skid proof, even wet, due to grain particles in the film
- Carrier: polyethylene based film
- Acrylic adhesive layer - no tape needed
- White colour for optimal light reflection
- Good chemical resistance
- Good dimensional stability and flatness
- Low electrostatic charge
- Good barrier to water vapor
- Resistant to oils and greases
- Good puncture, flex and crack resistance
- Clean removal, no residue up to 10 days
- Recyclable
- 25m on a roll
- Available in 60cm & 120cm width
- Thickness: 120 my
- Number of layers , minimum – maximum : 1/ 1
- Coverage = PRF 600: 15 m² per roll, PRF 1200: 30 m² per roll

3. Application

Surface preparation:

Remove all dirt, dust and grease from the surface on which the film is to be applied.

Applying the film on tables or small surfaces:

Unroll +/-30cm and position the film in the right direction.

Push the film out and remove air bubbles by rubbing by hand from the centre of the film to the outsides. Cut to the desired length.

Applying the film on floors or larger areas:

Unroll +/-30cm and position the film in the right direction.

Use a brush to push the film forward in the right direction.

Remove air bubbles by rubbing, using the brush from the centre of the film to the outsides.

4. Shelf life and storage:

Shelf life : 2 years

Storage: keep in a dry, well ventilated area, away from direct sunlight and frost.

Recommended storage temperature between 5°C-41°F and 25°C-77°F.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for

Chemicar Europe nv
Baarbeek 2
2070 Zwijndrecht
België-Belgium

T.: +32 3 234 87 80
F.: +32 3 234 87 89
info@chemicar.eu
www.chemicar.eu

specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.

Chemicar Europe nv
Baarbeek 2
2070 Zwijndrecht
België-Belgium

T.: +32 3 234 87 80
F.: +32 3 234 87 89
info@chemicar.eu
www.chemicar.eu