

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Anti-gravel coating paintable black - 11
UFI : 87A7-6HWF-NP9Q-1S7Y
Product code : AGB 01
Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Surface protection
Function or use category : Non industrial spraying, Industrial spraying

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Chemical Europe NV
Baarbeek 2
2070 Zwijndrecht
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemicar.eu

1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Extremely flammable liquid and vapour. Toxic to aquatic life with long lasting effects. May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

Danger

Contains :

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTRE or doctor if you feel unwell. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

Scandinavian countries regulation

Denmark

MAL code

: 5-3

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	(CAS-No.) 68920-06-9 (EC-No.) 920-750-0	25 – 50	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	2.5 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
Carbon black Substance with a Community workplace exposure limit	CAS: 1333-86-4	0.1-<1	
ethanol; ethyl alcohol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	0.1 – 1	Flam. Liq. 2, H225

Full text of H-statements: see section 16

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Allow affected person to breathe fresh air. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: No irritant effect.
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open.
First-aid measures after ingestion	: Do NOT induce vomiting. Obtain medical assistance.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: extinguishing powder. Carbon dioxide (CO ₂). Alcohol resistant foam. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting	: Approved respirator.
--------------------------------	------------------------

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing.
Emergency procedures	: Keep public away.

6.1.2. For emergency responders

Protective equipment	: Use personal protective equipment as required.
----------------------	--

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment	: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Provide adequate ventilation.
Methods for cleaning up	: Do not flush with water.

6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Ensure adequate air ventilation. Do not breathe vapours. Avoid formation of vapours.
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in dry protected location to prevent any moisture contact. Keep cool. Keep container tightly closed.
Storage area	: Store away from heat.
Special rules on packaging	: Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Anti-gravel coating paintable black - 1I		
DNEL/DMEL (Workers)		
Acute - systemic effects, dermal	0 mg/kg bodyweight/day	
Ingredients with limit values that require monitoring at the workplace:		
1333-86-4 Carbon Black		
Wel	Short-term value: 7mg/m ³	
	Long-term value: 3.5 mg/m ³	
64-17-5 Ethanol		
WEL	Long-term value: 1920 mg/m ³ , 1000 ppm	
DNEL's		
68920-06-9 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
		773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m ³ (Consumer)
		2.035 mg/m ³ (Worker)
Reaction mass of ethylbenzene en xylene		
Oral	DNEL Long term-systemic	1,6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer)
		180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	289 mg/m ³ (Worker)
	DNEL Long-term-systemic	14,8 mg/m ³ (Consumer)
		77 mg/m ³ (Worker)
PNEC's		
Reaction mass of ethylbenzene en xylene		
PNEC Freshwater	0,327 mg/l (Undefined)	
PNEC Marine water	0,327 mg/l (Undefined)	
PNEC Freshwater sediment	12,46 mg/l(dry weight) (Undefined)	
PNEC Soil	2,31 (Undefined)	
PNEC Sewage Treatment Plant	6,58 mg/l (Undefined)	
PNEC Marine water sediment	12,46 mg/l (dry weight) (Undefined)	

8.2. Exposure controls

Appropriate engineering controls:

Wash hands before breaks and after work. Do not breathe gas/vapour/aerosol.

Personal protective equipment:

Gas mask with filter type AX. Gas mask with filter type A. Gloves. EN 374. Protective goggles. EN 13034.

Materials for protective clothing:

Wear suitable protective clothing

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Condition	Material	Standard
		EN 13034

Hand protection:

Chemical resistant gloves (according to European standard EN 374 or equivalent). Solvent-resistant gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	5 (> 240 minutes), 6 (> 480 minutes)	>0.5		

Eye protection:

EN 166

Skin and body protection:

EN 13034

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
	Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust		

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 98 °C
Flash point	: 2 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 30 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.055 g/cm ³
Solubility	: Moderately soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Viscosity, kinematic	: 30 mm ² /s
Viscosity, dynamic	: 8000 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.7 vol %
Upper explosive limit (UEL)	: 7 vol %

9.2. Other information

VOC content	: 730.9 g/l
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
Additional information	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

Anti-gravel coating paintable black - 1I

Viscosity, kinematic	30 mm ² /s
----------------------	-----------------------

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD/LC50 values relevant for classification	
68920-06-9 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Oral LD50	>5000 mg/kg (rat)
Dermal LD50	>2800 mg/kg (Rabbit)
Inhalative LC50/4h	>23 mg/l (rat)
Reaction mass of ethylbenzene en xylene	
Oral LD50	4.300 mg/kg (rat)
Dermal LD50	2.000 mg/kg (rbt)

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Aquatic toxicity	
68920-06-9 Koolwaterstoffen, C7-C9, n-alkanen, iso-alkanen, cycliscs	
NOELR (72h)	10 mg/l (Pseudokirchneriella subcapitata)
EL50(48h)	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>13,4 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0,17 mg/l (Daphnia magna)
LOEC (21 days)	0,32 mg/l (Daphnia magna)
EC50/48h	3 mg/l (Daphnia magna)
Reaction mass of ethylbenzeee en xylene	
NOEC	1,3 mg/l (Fish)
NOEC (7 day)	0,96 mg/l (Daphnia magna)
NOEC (72h)	0,44 mg/l (algae)
NOEC (28 d)	16 mg/l (Bacteria)
LC 50/96h	8,9-16,4 mg/l
EC50/48h	3,2-9,5 mg/l (Daphnia magna)

12.2. Persistence and degradability

Anti-gravel coating paintable black - 1I

Persistence and degradability : Readily biodegradable.

12.3. Bioaccumulative potential

Anti-gravel coating paintable black - 1I

Bioaccumulative potential : Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Anti-gravel coating paintable black - 1I

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Do not dispose of with domestic waste. Do not discharge into drains.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

SECTION 14: Transport information


In accordance with ADR / IATA / IMDG / ADN

ADR	IMDG	IATA	ADN
14.1. UN number			
UN 1139	UN 1139	UN 1139	UN 1139
14.2. UN proper shipping name			
COATING SOLUTION	COATING SOLUTION	Coating solution	Not applicable
Transport document description			
UN 1139 COATING SOLUTION (), 3, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1139 COATING SOLUTION, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1139 Coating solution, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1139 , ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
3	3	3	Not applicable
14.4. Packing group			
III	III	III	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F2
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Transport category (ADR) : 3
Hazard identification number (Kemler No.) : --
Orange plates :



Tunnel restriction code (ADR) : E

Transport by sea

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

No data available

Inland waterway transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on
3.	xylene
3(a)	xylene
3(b)	xylene
40.	xylene

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 730.9 g/l

15.1.2. National regulations

Netherlands

Waterbezwaarlijkheid : 1 - Black list substance
SZW-lijst van kankerverwekkende stoffen : ethanol; ethyl alcohol is listed
SZW-lijst van mutagene stoffen : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : ethanol; ethyl alcohol is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : ethanol; ethyl alcohol is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : xylene, ethanol; ethyl alcohol are listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Anti-gravel coating paintable black - 1I

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
DNEL	Derived-No Effect Level
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.