

TECHNICAL SHEET

BTG 05 - Finixa plastic and tyre renovator black 0.5kg

Physical properties

| | |
|---|-----------------------------------|
| Physical state | Paste |
| Colour | black |
| Odour | characteristic |
| Initial boiling point and boiling range | 82 |
| Flash point | 26,5 °C Not sustaining combustion |
| Ignition temperature in °C | 425 |
| VOC-value (in g/L): | 10,042 % (99,411 g/l) |

Analytic dates

| | |
|-----------|------------------------|
| pH | 8,1 |
| Viscosity | 9000-14000 mPa s |
| Density | 0,99 g/cm ³ |

Technical data

| | |
|-------------|-------------|
| Gloss level | 6 – Extreme |
|-------------|-------------|

Shelf life and storage conditions

| | |
|---------------------|-------------|
| Shelf life | 2 years |
| Storage temperature | 15°C - 25°C |

Application

Finixa black tyre gel can be applied with the POL 33 foam pad to make tires deep black and leaving them shining for a very long time. Also suitable to refurbish non painted plastic parts.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.