

## **TECHNICAL DATA SHEET**

### **CLM 05 –Liquid Masking wall protection - washable 5l**

#### **Description**

Liquid Masking wall protection - washable film to protect against overspray, washable with water.

#### **Technical information**

Colour:	Troubled transparant.
Flashpoint:	NA – resist heat 65 C°
Viscosity:	Standard ca 250 cps with SP5 / 100T/min Brookfield RVT
Ph:	+/- 7-9
VOC:	< 0,5 %
ADR/danger:	No
Density:	1,04 g / cm <sup>3</sup>
Film:	Transparant, sticky.
Return:	ca 20m <sup>2</sup> / liter

#### **Application**

Liquid Masking wall protection - washable Foil is a liquid gast drying product to protect all kinds of non porous undergrounds. Protects against dirty, dust and overspray.  
After applying remove with water.

#### **Treatment**

With Spray gun: → Nozzle: 1.3  
→ Pressure: 1,5 to 2,0 bar

#### **Safety regulation**

Avoid long contact with the skin. Wash hands thoroughly. In case of eye contact please rinse very long with water. Check the MSDS for further details.  
The product is considered as not dangerous and is chemically decomposable.

#### **Maintenance and storage life**

KEEP FROM FROST, do not store above 30°C, keep away from direct sun  
Shelf life: 2 ans  
Do not use at a temperature underneath 5°C.

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.*