

TECHNICAL SHEET

DZB – Finixa double sided tape

Description

Finixa double sided tape is a reinforced acrylic foam tape with high tack and shear strength performance acrylic adhesive. The product has excellent adhesion to a wide range of substrates including plastics & metals. Ideal for bonding emblems, nameplates, plastic panels and metals.

Technical



Shelf life

2 years

Physical properties

Values shown are typical values and not to be used for specification purposes.

Carrier	Acrylic Foam Base, Grey
Liner	Red PE Film
Adhesive	High Tack Acrylic (Solvent Based)
Thickness	1.1mm (+/- 0.05mm)
Width	9mm, 12mm, 19mm and 25mm (+/- 1mm)
Length	10m (+/- 0.1m)

Performance properties

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	1900gf/10mm - 80°C x 250hrs
Static Shear	23°C; 1500g load; OK 93°C; 500g load; OK
Dynamic Shear	7.1kgf/cm ² - 80°C x 250hrs - 10mmx10mm
Temperature Resistance	120°C

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.