

TECHNICAL SHEET

FOL 62 – Finixa logo tape adhesive transfer

Description

Finixa logo tape is a system provided with a controlled cohesion special transfer excellent for a total and clean release on the surfaces with which it comes into contact. Purposely designed for recovering logos and emblems of all types of vehicles. It is also ideal for positioning parts before final fixing or for fixing decorative and promotional items.

Logo tape is available in holders of 10 strips each.

Technical data

Sizes:	L300mm x H60mm (300mm x 50mm adhesive surface only)
Thickness of adhesive film:	0,04mm (*)
Thickness of tape:	0,08mm (*)
Adhesion on steel:	74N/100mm (*)
Application temperature:	+15°C – +35°C

(*) All above data are approximate

How to use

Remove the emblem or logo from vehicle by cutting its original adhesive. Thoroughly clean the old foam on the logo with an antislip product and wait until completely dry. With same product thoroughly clean also the surface where the logo will be fixed. Remove the red liner from the logo tape and place the logo with its back side in contact with the double-sided adhesive film of logo tape and apply a uniform manual pressure. Raise the logo from the adhesive strip. Place the logo on vehicle and apply a uniform manual pressure all over the logo.

Storage and shelf life

Finixa logo tape stored in its original package, in a dry and well ventilated place, at a temperature between +5°C and +35°C has a shelf life: 2 years.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.