



|               | COLOUR                | APPLICATION |           |            |           |                |            |              |              |                      | APPEARANCE         |                          | MIXING           |                       | DRYING             |                     |           | PAGE |
|---------------|-----------------------|-------------|-----------|------------|-----------|----------------|------------|--------------|--------------|----------------------|--------------------|--------------------------|------------------|-----------------------|--------------------|---------------------|-----------|------|
|               |                       | STEEL       | E-COATING | GALVANIZED | ALUMINIUM | ALUMINIUM RIMS | FIBERGLASS | HARD PLASTIC | SOFT PLASTIC | SPECIFIC WEIGHT kg/l | PACKAGING kg/liter | MIXING RATIO % by weight | POTLIFE at 20°C. | SANDING TIME AT 20°C. | SANDING TIME 60°C. | TEMP. RESISTANCE °C |           |      |
| <b>GAP 00</b> | <b>GAPOL</b>          | ●●          | ●●        | ●●         | ●●        | ●●             | ●●         | ●●           | ●●           | 1,83                 | 2kg/1,09l          | 2%                       | 4-5'             | <25'                  | 10'                | 80 °C               | <b>64</b> |      |
| <b>GAP 10</b> | <b>MULTI</b>          | ●●          | ●●        | ●          | ●         |                | ●●         |              |              | 1,81                 | 2kg/1,10l          | 2%                       | 4-5'             | <20'                  | 5'                 | 80 °C               | <b>64</b> |      |
| <b>GAP 20</b> | <b>FINE</b>           | ●●          | ●●        |            |           |                | ●          |              |              | 1,68                 | 2kg/1,19l          | 2%                       | 4-5'             | <15'                  | 10'                | 80 °C               | <b>64</b> |      |
| <b>GAP 25</b> | <b>SELF-LEVELLING</b> | ●●          | ●●        |            |           |                | ●          |              |              | 1,16                 | 1kg/0,85l          | 2%                       | 3'               | 15-20'                | 5-10'              | 80 °C               | <b>65</b> |      |
| <b>GAP 30</b> | <b>LIGHT</b>          | ●●          | ●●        | ●          | ●         |                | ●●         |              |              | 1,36                 | 1,5kg/1,09l        | 2%                       | 4-5'             | <15-20'               | 5-10'              | 80 °C               | <b>66</b> |      |
| <b>GAP 31</b> | <b>ULTRA LIGHT</b>    | ●●          | ●         | ●          | ●         |                | ●●         |              |              | 1                    | 1kg/1l             | 1-3%                     | 3-5'             | <30'                  | 4'-5'              | 80 °C               | <b>66</b> |      |
| <b>GAP 33</b> | <b>EXTRA LIGHT</b>    | ●●          | ●         | ●          | ●         |                | ●●         |              |              | 1                    | 3kg/3l             | 1-3%                     | 3-5'             | <30'                  | 4'-5'              | 80 °C               | <b>66</b> |      |
| <b>GAP 40</b> | <b>FIBER</b>          | ●           |           |            | ●         |                | ●●         |              |              | 1,61                 | 1,8kg/1,11l        | 2%                       | 4-5'             | <20'                  | 10'                | 80 °C               | <b>67</b> |      |
| <b>GAP 50</b> | <b>ALU</b>            | ●●          | ●●        | ●●         | ●●        | ●●             | ●          |              |              | 1,53                 | 2kg/1,30l          | 2%                       | 4-6'             | <20'                  | 10'                | 80 °C               | <b>67</b> |      |
| <b>GAP 70</b> | <b>PLASTFILL</b>      |             |           |            |           |                | ●          | ●            | ●            | 1,3                  | 1kg/0,75l          | 1-3%                     | 3-5'             | <30'                  | 4'-5'              | 80 °C               | <b>68</b> |      |
| <b>GAP 80</b> | <b>UV</b>             | ●●          | ●●        | ●          | ●         |                | ●●         | ●●           |              | 1,75                 | 500 gr cartridge   | -                        | ∞                | -                     | 2'-5' @7mW/cm²     | 80 °C               | <b>69</b> |      |
| <b>GAP 90</b> | <b>LIGHT AND EASY</b> | ●●          | ●●        | ●●         |           |                | ●          | TSP 030      | TSP 030      | 1,24                 | 1,9kg/1,5l         | 2%                       | 3-4'             | 15-20'                | 5-10'              | 80 °C               | <b>70</b> |      |
| <b>GAP 93</b> | <b>LIGHT AND EASY</b> | ●●          | ●●        | ●●         |           |                | ●          | TSP 030      | TSP 030      | 1,24                 | 3,9kg/3l           | 2%                       | 3-4'             | 15-20'                | 5-10'              | 80 °C               | <b>70</b> |      |
| <b>DEB 12</b> | <b>PB - SN</b>        | ●●          | ●●        | ●●         | ●●        | ●●             |            | TSP 030      | TSP 030      | 1,3                  | 1L/1,3kg           | 1-3%                     | 3-4'             | <30'                  | -                  | 180° C MAX 15'!     | <b>67</b> |      |

### Hardener

- GAP 51** For all GAP putties
- DEB 51** For DEB 12
- GAP 80** No hardener needed

### Storage

Shelf life putty: 18 months  
Shelf life BPO hardener: 12 months

- Very suitable
- Suitable



Dry



Frost free



Not in direct sunlight



Closed tin