

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Finixa polyester putty 1.5kg + hardener - light
UFI	: CRU7-AMYA-U10H-M7XR
Product code	: GAP 30
Product group	: Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Chemical Europe NV
Baarbeek, 2
2070 Zwijndrecht
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemical.eu

1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 2	H361d
Specific target organ toxicity – Repeated exposure, Category 1	H372
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: styrene; 2,2'-(m-tolylimino)diethanol; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2- ((2-(2-hydroxyethoxy)ethyl)(4-methylphenyl)amino)-; maleic anhydride

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	H319 - Causes serious eye irritation.
	H361d - Suspected of damaging the unborn child.
	H372 - Causes damage to organs (hearing organs) through prolonged or repeated exposure (In case of repeated or prolonged exposure :).
	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260 - Do not breathe dust, fume, gas, mist.
	P280 - Wear protective gloves, protective clothing, eye protection, face protection, hearing protection.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P403+P235 - Store in a well-ventilated place. Keep cool.

Nordic countries regulation

Denmark

MAL code : 4-6

2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0	10 – 20	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319
2,2'-(m-tolylimino)diethanol	CAS-No.: 91-99-6 EC-No.: 202-114-8	0.1 – 1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2- ((2-(2-hydroxyethoxy)ethyl)(4-methylphenyl)amino)-	EC-No.: 911-490-9	0.1 – 1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
maleic anhydride	CAS-No.: 108-31-6 EC-No.: 203-571-6	0.001 – 0.1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 1, H372

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Take off immediately all contaminated clothing.
First-aid measures after inhalation	: In case of loss of consciousness, place the victim in the recovery position. Allow affected person to breathe fresh air. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: After contact with skin, wash immediately with plenty of water and soap.
First-aid measures after eye contact	: Rinse opened eye for several minutes under running water. Then consult doctor.
First-aid measures after ingestion	: Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. extinguishing powder. Water spray jet. For large fire: Alcohol resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: At high temperature may liberate toxic gases. Toxic products produced by burning.
--	---

5.3. Advice for firefighters

Protection during firefighting	: [In case of inadequate ventilation] wear respiratory protection.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable protective clothing. Warn road users and passers by to keep away from danger area.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Use personal protective equipment as required.
----------------------	--

6.2. Environmental precautions

Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel).
Other information	: SECTION 13. Provide adequate ventilation.

6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Remove contaminated clothes.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed.
- Storage area : Store in a well-ventilated place.
- Special rules on packaging : Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
SECTION 7.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection

Type	Field of application	Characteristics	Standard
Protective goggles			

8.2.2.2. Skin protection

Hand protection:
protective gloves

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Viton		≥ 0,7 mm	3 (> 0.65)	

8.2.2.3. Respiratory protection

Respiratory protection			
Device	Filter type	Condition	Standard
Self-contained breathing apparatus (SCBA)	Type P2		EN 143

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Beige.
Appearance	:
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: 145 °C (100-42-5 styreen)
Flammability	: Not self-igniting
Explosive limits	: Not available
Lower explosion limit	: 1.2 vol % (100-42-5 styreen)
Upper explosion limit	: 8.9 vol %
Flash point	: 34 °C (DIN 53213)
Auto-ignition temperature	: 480 °C (DIN 51794, 100-42-5 styreen)
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 80000 – 95000 mPa·s
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 6 hPa (100-42-5 styreen)
Vapour pressure at 50°C	: Not available
Density	: 1.402 g/cm³ (DIN 53217)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	: 1.45 %
Additional information	: Solid content 82,5%. The product is not explosive. Flammable or explosive vapour/air mixtures may be formed

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: May produce an allergic reaction
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs (hearing organs) through prolonged or repeated exposure (In case of repeated or prolonged exposure :).

styrene (100-42-5)

STOT-repeated exposure	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
------------------------	--

2,2'-(m-tolylimino)diethanol (91-99-6)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

maleic anhydride (108-31-6)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified

11.2. Information on other hazards

Endocrine disrupting properties

78-93-3	Methyl ethyl ketone	List II
128-37-0	Butylated hydroxytoluene	List II

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

Finixa polyester putty 1.5kg + hardener - light

Ecology - soil	Do not flush into surface water or sewer system. May cause long-term adverse effects in the aquatic environment. Hazardous to water (WGK 2).
----------------	--

12.5. Results of PBT and vPvB assessment

Finixa polyester putty 1.5kg + hardener - light

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : Refer to section 11.

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Do not dispose of with domestic waste.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
European List of Waste (LoW, EC 2150/2002)	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information




In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number or ID number			
UN 3269	UN 3269	UN 3269	Not applicable
14.2. UN proper shipping name			
POLYESTER RESIN KIT	POLYESTER RESIN KIT	Polyester resin kit	Not applicable

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN
Transport document description			
UN 3269 POLYESTER RESIN KIT (), 3, III, (E)	UN 3269 POLYESTER RESIN KIT, 3, II	UN 3269 Polyester resin kit, 3, II	Not applicable
14.3. Transport hazard class(es)			
3	3	3	Not applicable
			Not applicable
14.4. Packing group			
III	II	II	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Not applicable
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F3
Special provisions (ADR)	: 236, 340
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P302, R001
Transport category (ADR)	: 3
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: E
EAC code	: •2YE

Transport by sea

Special provisions (IMDG)	: 236, 340
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: SP340
Packing instructions (IMDG)	: P302
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Polyester resin kits consist of two components: a base material (flammable liquid, packaging group II) and an activator (organic peroxide), each separately packed in an inner packaging.

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y370
PCA limited quantity max net quantity (IATA)	: 1kg
PCA packing instructions (IATA)	: 370
PCA max net quantity (IATA)	: 5kg
CAO packing instructions (IATA)	: 370
CAO max net quantity (IATA)	: 5kg
Special provisions (IATA)	: A66, A163
ERG code (IATA)	: 3L

Inland waterway transport

Not applicable

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 1.45 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 66	Occupational rhinitis and asthma

Germany

Water hazard class (WGK)	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Storage class (LGK, TRGS 510)	: LGK 3 - Flammable liquids.
Chemicals Prohibition Ordinance (ChemVerbotsV)	: This product is subject to ChemVerbotsV Annex 2 Entry 1. The following requirements must be observed: authorization requirement (according to § 6 paragraph 1 sentence 1), basic requirements for carrying out the delivery (according to § 8 paragraph 1, 3 and 4), identification and documentation (according to § 9 paragraph 1 to 3) and exclusion of the shipping route (according to § 10).
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

Waterbezwaarlijkheid	: 10 - Weinig schadelijk voor in het water levende organismen; kan in het aquatisch milieu op lange termijn schadelijke effecten veroorzaken.
Saneringsinspanningen	: A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : styrene is listed

Denmark

Class for fire hazard : Class II-1

Store unit : 5 liter

Classification remarks : R10 <H226;H315;H317;H319;H361d;H372>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Finixa polyester putty 1.5kg + hardener - light

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.