

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Polyester putty 3kg + hardener - light
UFI : YP27-E8SE-7QC7-323M
Product code : GAP 31

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only
Use of the substance/mixture : Fillers, putties, plasters, modelling clay

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Chemical Europe NV
Baarbeek 2
2070 Zwijndrecht
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemical.eu

1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

| | |
|--|-------|
| Flammable liquids, Category 3 | H226 |
| Skin corrosion/irritation, Category 2 | H315 |
| Serious eye damage/eye irritation, Category 2 | H319 |
| Skin sensitisation, category 1A | H317 |
| Reproductive toxicity, Category 2 | H361d |
| Specific target organ toxicity — Repeated exposure, Category 1 | H372 |
| Full text of H statements : see section 16 | |

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS07



GHS08

Signal word (CLP) :

Danger

Contains :

styrene

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|--------------------------------|--|
| Hazard statements (CLP) | : H226 - Flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H361d - Suspected of damaging the unborn child. H372 - Causes damage to organs through prolonged or repeated exposure. |
| Precautionary statements (CLP) | : P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe vapours. P280 - Wear protective gloves, eye protection. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. |

Scandinavian countries regulation

Denmark

MAL code : 4-6

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|----------------------------|--|------------|---|
| styrene | (CAS-No.) 100-42-5 (EC-No.) 202-851-5 (EC Index-No.) 601-026-00-0 | 15 – 20 | Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319 |
| xylene | (CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 | 1 – 3 | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 |
| isopentane; 2-methylbutane | (CAS-No.) 78-78-4 (EC-No.) 201-142-8 (EC Index-No.) 601-085-00-2 | 0.1 – 0.25 | Flam. Liq. 1, H224 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 |
| maleic anhydride | (CAS-No.) 108-31-6 (EC-No.) 203-571-6 | 0.01 – 0.1 | Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 1, H372 |

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures after inhalation | : Then ventilate the premises. Move the affected person away from the contaminated area and into the fresh air. Call a doctor. |
| First-aid measures after skin contact | : Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. After contact with skin, wash immediately with plenty of water and soap. |

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|--------------------------------------|--|
| First-aid measures after eye contact | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| First-aid measures after ingestion | : Do NOT induce vomiting. Get immediate medical advice/attention. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|------------------|--|
| Symptoms/effects | : Refer to chapter 8. For further information refer to section 13. |
|------------------|--|

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Carbon dioxide (CO ₂). dry extinguishing powder. |
| Unsuitable extinguishing media | : Do not use extinguishing media containing water. Cool containers / tanks with spray water if possible. Do not use water jet. |

5.2. Special hazards arising from the substance or mixture

| | |
|--|--|
| Fire hazard | : In case of fire and/or explosion do not breathe fumes. |
| Hazardous decomposition products in case of fire | : Fire will produce dense black smoke. |

5.3. Advice for firefighters

| | |
|--------------------------------|--|
| Firefighting instructions | : Prevent fire fighting water from entering the environment. Do not flush down sewers. |
| Protection during firefighting | : Approved respirator. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|---|
| General measures | : Wear personal protective equipment. Evacuate area. Remove ignition sources. |
|------------------|---|

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Notify authorities if product enters sewers or public waters. Take up liquid spill into inert absorbent material. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel).

6.3. Methods and material for containment and cleaning up

| | |
|-----------------|--|
| For containment | : Dike for recovery or absorb with appropriate material. |
|-----------------|--|

6.4. Reference to other sections

SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|--|
| Additional hazards when processed | : Avoid contact with eyes. Avoid contact with skin, eyes and clothing. Avoid breathing dust, mist or spray. Take off contaminated clothing. When using do not eat, drink or smoke. |
|-----------------------------------|--|

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

| | |
|--------------------|---|
| Technical measures | : Ensure adequate ventilation. Keep cool. Protect from sunlight. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. |
| Storage conditions | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from food, drink and animal feeding stuffs. |

7.3. Specific end use(s)

1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| | |
|---|--|
| 100-42-5 Styrene | |
| EU- TWA(8h) STEL() | 85 mg/M3, 20 ppm 170 mg/m3, 40 ppm Notes: Pelle |
| ACGIH – TWA (8H) STEL | 10 ppm 20 ppm Notes: OTO, A3,BEI |
| Italy – TWA(8h) STEL | CNS and hearing impair, URT irr, peripheral neuropathy, visual disorders 20 ppm 200 ppm |
| 1130-20-7 Xylene | |
| Italy – WAS(8h) STEL() | 221 mg/m3, 50 ppm 442 mg/M3, 100 ppm – Notes Assorbito attraverso la pelle ACGIH - TWA(8u): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair UE - TWA(8u): 221 mg/m3, 50 ppm - STEL: 442 mg/m3, 100 ppm - Notes: Skin |
| 78-78-4 Isopentaa | |
| UE - TWA(8u) ACGIH – TWA(8h) | 3000 mg/m3, 1000 ppm 1000 ppm - Notes: Narcosis, resp tract irr |
| 108-31-6 maleic anhydride | |
| ACGIH – TWA(8h) | 0.01 mg/m3 - Notes: (IFV), DSEN, RSEN, A4 - Resp sens |
| DNEL Exposure Limit Values | |
| 100-42-5 styrene | |
| Worker Professional Consumer Exposure | 406 mg/kg 343 mg/kg Human Dermal - Frequency: Long Term, systemic effects Consumer: 2.1 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects – Worker Professional: 85 mg/m³ - Consumer: 10.2 mg/m³ - Exposure: Human Inhalation – Frequency: Long Term, systemic effects Worker Professional: 289 mg/m³ - Consumer: 174.25 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects Worker Professional: 306 mg/m³ - Consumer: 182.75 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects |
| 1330-20-7 Xylene | |
| | Worker Professional: 442 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects Worker Professional: 212 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal – Frequency: Long Term, systemic effects Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Worker Professional: 212 mg/kg - Consumer: 125 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated) Worker Professional: 221 mg/m³ - Consumer: 65.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term (repeated) Consumer: 12.5 mg/kg/day - Exposure: Human Oral - Frequency: Long Term (repeated) |
| PNEC Exposure Limit Values | |
| 100-425 Styrene | |
| Target | Fresh Water - Value: 0.028 mg/l Marine water - Value: 0.028 mg/l Freshwater sediments - Value: 0.614 mg/kg Marine water sediments - Value: 0.0614 mg/kg Soil (agricultural) - Value: 0.2 mg/kg Value: 0.04 mg/l Purification plant - Value: 5 mg/l |

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1330-20-7 Xylene

| | |
|--------|---|
| Target | Purification plant - Value: 6.58 mg/l T Marine water - Value: 0.32 mg/l Intermittent emissions - Value: 0.32 mg/l Freshwater sediments - Value: 12.46 mg/kg Marine water sediments - Value: 12.46 mg/kg Soil - Value: 2.31 mg/kg Fresh Water - Value: 0.32 mg/l |
|--------|---|

Biological Exposure Index

100-42-5 styrene

Value: 400 mg/g creatinine - medium: Urine - Biological Indicator: Mandelic acid in urine and fenilgliossilico - Sampling Period: End of turn Value: 40 mg/l creatinine - medium: Urine - Biological Indicator: Styrene in urine - Sampling Period: End of turn

1330-20-7 Xylene

Value: 1.5 g/g - medium: Urine - Biological Indicator: Creatinine in urine - Sampling Period: End of turn

8.2. Exposure controls

Materials for protective clothing:

Wear suitable protective clothing

| Condition | Material | Standard |
|-----------|----------|----------|
| | | EN 14605 |

Hand protection:

| Type | Material | Permeation | Thickness (mm) | Penetration | Standard |
|------|----------|------------------|----------------|-------------|------------|
| | | 3 (> 60 minutes) | 0.4 | | EN ISO 374 |

Eye protection:

Protective goggles

Skin and body protection:

Take off immediately all contaminated clothing.

| Type | Standard |
|------|----------|
| | EN 14605 |

Respiratory protection:

| Device | Filter type | Condition | Standard |
|--------|---|-----------|----------|
| | Type A - High-boiling (>65 °C) organic compounds | | |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---------------------|
| Physical state | : No data available |
| Appearance | : Paste. |
| Colour | : Yellow. |
| Odour | : styrene. |
| Odour threshold | : 0.15 – 0.25 ppm |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : 145 °C |

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|---|---------------------|
| Flash point | : 32 °C |
| Auto-ignition temperature | : 490 °C |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : 6.7 hPa |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : 1000 g/cm³ |
| Density | : 3.6 |
| Solubility | : Insoluble. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Viscosity, kinematic | : > 20.5 mm²/s |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Lower explosive limit (LEL) | : 1.1 vol % |
| Upper explosive limit (UEL) | : 8 vol % |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Oxidant. Strongly supports combustion. May react violently with combustible materials.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------------|---|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Suspected of damaging the unborn child. |
| STOT-single exposure | : Not classified |

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Polyester putty 3kg + hardener - light

Viscosity, kinematic > 20.5 mm²/s

Toxicological information of the main substances found in the product

100-42-5 Styrene

| | | |
|-------------------------|--|---|
| acute toxicity: | Test: LD50 Test: LC50 | Route: Oral - Species: Rat = 5000 mg/kg Inhalation - Species: Rat = 11.8 mg/l - Duration: 4h |
| STOT-repeated exposure: | Test: LD50 Test: LOAEL(C) Test: NOAEL(C) Test: LOAEL(C) | Route: Skin - Species: Rat > 2000 mg/kg - Notes: OECD 402 Route: Oral - Species: Rat = 2000 mg/kg - Notes: bw/day Route: Oral - Species: Rat = 1000 mg/kg - Notes: bw/day Route: Inhalation - Species: Rat = 0.21 mg/l |

1330-20-7 Xylene

| | | |
|--------------------|--|--|
| a) acute toxicity: | Test LC 50 - Route: Inhalation – Species Test: LD50 - Route: Oral – Species Test: LD 50 – Route Skin – Species | Rat = 6700 ppm - Duration: 4h Rat = 5627 mg/kg Rabbit > 5000 mg/kg |
|--------------------|--|--|

100-42-5 Styrene

Acute inhalation toxicity at 1000 ppm affects the central nervous system with headaches, dizziness and coordination difficulties; irritation of the mucous membranes of the eyes and respiratory tract occurs at 500 ppm. Chronic exposure gives system depression central and peripheral nervous system with memory loss, headaches and somnolence starting from 20 ppm; digestive disorders with nausea e loss of appetite; respiratory tract irritation with chronic bronchitis; dermatosis. Repeated exposure, to low doses of the substance by inhalation, it causes irreversible changes in hearing function and can cause changes in color vision. Repeated skin exposures cause irritation. The substance degrades the skin, which can cause dryness and cracking

1330-20-7 Xylene

Inhalation: Harmful if inhaled. Very high concentrations of xylene lead to the progressive inhibition of the central nervous system (CNS), followed by coma, respiratory weakness, and finally absence of cerebral blood flow and death. High concentrations cause coma and respiratory weakening, destabilize the function of the kidneys and lead to liver damage. At low concentrations, irritation of the eyes, nasopharynx, illness, irritation, slow reaction times and reduced short-term memory occur. Vapors of xylene can cause dizziness, headache, nausea, mental confusion. Ingestion: In the event of ingestion of xylene, the injured person has a burning sensation and stomach ache, in case of aspiration there is a danger of chemical pneumonitis and pulmonary edema. Skin Contact: May be harmful if absorbed through the skin. Causes skin irritation. Contact with eyes: Vapors of xylene and xylene in liquid form irritate the eyes and membranes.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

100-42-5 Styrene

| | | |
|--------------------------|---|---|
| Aquatic acute toxicity | Endpoint: LC50 – Species: Fish Endpoint: EC 50 – Species: Algae Endpoint EC 50 - Species: Daphnia | 4.02 mg/l - Duration h: 96 4.9 mg/l - Duration h: 72 4.7 mg/kg - Duration h: 48 |
| Aquatic chronic toxicity | Endpoint: EC10 - Species: Algae Endpoint: NOEC – Species: Daphnia | 0.28 mg/l - Duration h: 96 1.01 mg/l - Duration h: 504 |

1330-20-7 Xylene

| | | |
|------------------------|--|--|
| Aquatic acute toxicity | Endpoint: NOEC – Species: Daphnia Endpoint – Species: Algae Endpoint: LC50 - Species: Fish Endpoint: NOEC - Species: Algae Endpoint: NOEC - Species: Daphnia Endpoint: NOEC - Species: Fish | 1 mg/l - Duration h: 24 4.36 mg/l - Duration h: 73 2.6 mg/l - Duration h: 96 0.44 mg/l - Duration h: 73 1.57 mg/l - Duration h: 504 1.3 mg/l - Duration h: 1344 |
|------------------------|--|--|

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available



SECTION 13: Disposal considerations

13.1. Waste treatment methods

No additional information available

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

| ADR | IMDG | IATA | ADN |
|---|---|----------------|----------------|
| 14.1. UN number | | | |
| UN 3269 | UN 1263 | Not applicable | Not applicable |
| 14.2. UN proper shipping name | | | |
| POLYESTER RESIN KIT | PAINT | Not applicable | Not applicable |
| Transport document description | | | |
| UN 3269 POLYESTER RESIN KIT, 3, III, (E) | UN 1263 PAINT, 3, III | Not applicable | Not applicable |
| 14.3. Transport hazard class(es) | | | |
| 3 | 3 | Not applicable | Not applicable |
|  |  | Not applicable | Not applicable |
| 14.4. Packing group | | | |
| III | III | Not applicable | Not applicable |
| 14.5. Environmental hazards | | | |
| Dangerous for the environment : No | Dangerous for the environment : No Marine pollutant : No | Not applicable | Not applicable |
| No supplementary information available | | | |

14.6. Special precautions for user

Overland transport

| | |
|---|--------------|
| Classification code (ADR) | : F3 |
| Special provisions (ADR) | : 236, 340 |
| Limited quantities (ADR) | : 5I |
| Excepted quantities (ADR) | : E0 |
| Packing instructions (ADR) | : P302, R001 |
| Transport category (ADR) | : 3 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Tunnel restriction code (ADR) | : E |

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EAC code : •2YE

Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

Not applicable

Inland waterway transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC Directive (2004/42)

VOC content : 17.473 % 1000 gr

15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen – Borstvoeding

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen – Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen – Ontwikkeling

Denmark

Class for fire hazard : Class II-1

Store unit : 5 liter

Classification remarks : R10 <H226;H315;H317;H319;H361d;H372>; Emergency management guidelines for the storage of flammable liquids must be followed

Polyester putty 3kg + hardener - light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment — Chronic Hazard, Category 2 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 1 | Flammable liquids, Category 1 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Repr. 2 | Reproductive toxicity, Category 2 |
| Skin Corr. 1B | Skin corrosion/irritation, Category 1, Sub-Category 1B |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT RE 1 | Specific target organ toxicity — Repeated exposure, Category 1 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H224 | Extremely flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H361d | Suspected of damaging the unborn child. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.