

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Polyester putty 3kg + hardener - extra light
UFI : YP27-E8SE-7QC7-323M
Product code : GAP 33

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only
Use of the substance/mixture : Fillers, putties, plasters, modelling clay

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Chemical Europe NV
Baarbeek, 2
2070 Zwijndrecht
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemicar.eu

1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Reproductive toxicity, Category 2	H361d
Specific target organ toxicity – Repeated exposure, Category 1	H372

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: styrene

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)

- H361d - Suspected of damaging the unborn child.
- H372 - Causes damage to organs through prolonged or repeated exposure.
- : P202 - Do not handle until all safety precautions have been read and understood.
- P260 - Do not breathe vapours.
- P280 - Wear protective gloves, eye protection.
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0	15 – 20	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319
xylene	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	1 – 3	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
isopentane; 2-methylbutane	CAS-No.: 78-78-4 EC-No.: 201-142-8 EC Index-No.: 601-085-00-2	0.1 – 0.25	Flam. Liq. 1, H224 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
2,2'-(m-tolylimino)diethanol	CAS-No.: 91-99-6 EC-No.: 202-114-8	0.1 – 0.25	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373
maleic anhydride	CAS-No.: 108-31-6 EC-No.: 203-571-6	0.01 – 0.1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 1, H372

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. Then ventilate the premises. medical advice.
- First-aid measures after skin contact : Take off immediately all contaminated clothing. Rinse skin with water/shower. After contact with skin, wash immediately with plenty of water and soap. Remove contaminated clothing.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Protect undamaged eye.
- First-aid measures after ingestion : Do NOT induce vomiting. Get immediate medical advice/attention.

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Refer to chapter 8. For further information refer to section 13.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO₂). dry extinguishing powder.
Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Do not breathe gas. On combustion forms: fume.

5.3. Advice for firefighters

Firefighting instructions : Do not allow run-off from fire-fighting to enter drains or water courses. Contain and collect extinguishing water.
Protection during firefighting : Breathing apparatus.
Other information : Drums. Evacuate danger area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear personal protective equipment. Evacuate area. Remove ignition sources.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow material to contaminate ground water system. Do not allow to enter drains or water courses. Dispose of rinse water as waste water. In case of contamination of soil or water bodies notify the competent authorities. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel).

6.3. Methods and material for containment and cleaning up

For containment : Dike for recovery or absorb with appropriate material.

6.4. Reference to other sections

SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Avoid contact with eyes. Avoid contact with skin, eyes and clothing. Avoid breathing dust, mist or spray. Take off contaminated clothing. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation. Keep cool. Protect from sunlight. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.
Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from food, drink and animal feeding stuffs.

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.3. Specific end use(s)

1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Styreen (100-42-5)		
EU	TWA(8h)	85 mg/m3, 20 ppm - STEL(): 170 mg/m3, 40 ppm - Notes: Pelle
EU	ACGIH - TWA(8h)	20 ppm - STEL: 40 ppm - Notes: A4, BEI - CNS impair, URT irr, peripheral neuropathy, visual disorders
Italy	TWA(8u)	20 ppm – STEL: 200 ppm
xyleen (1330-20-7)		
Italy	IOELV TWA (mg/m³)	221 mg/m³
	IOELV TWA (ppm)	50 ppm
	IOELV STEL (mg/m³)	442 mg/m³
	IOELV TWA (ppm)	100 ppm
Opmerkingen: Assorbito attraverso la pelle		
	ACGHIH TWA (8u)	100 ppm
	IOELV STEL (mg/m³)	442 mg/m³
	IOELV TWA (ppm)	100 ppm
Opmerkingen : skin		
Isopentaan (78-78-4)		
EU	TWA(8h)	TWA(8u): 3000 mg/m3, 1000 ppm
ACGIH	TWA(8u)	1000 ppm
Narcosis, resp tract irr		
maleïnezuuranhydride (108-31-6)		
ACGIH	TWA(8u)	0.01 mg/m3
Opmerkingen: (IFV), DSEN, RSEN, A4 - Resp sens		
DNEL exposure limit values		
Styrene (100-42-5)		
Worker Professional	406 mg/kg - Consumer: 343 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects	
Consumer	2.1 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects	
Worker Professional	85 mg/m³ - Consumer: 10.2 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects	
Worker Professional	289 mg/m³ - Consumer: 174.25 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects	
Worker Professional	306 mg/m³ - Consumer: 182.75 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects	
Xylene (1330-20-7)		
Worker Professional	442 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects	
Worker Professional	212 mg/kg - Consumer: 125 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects	
Worker Professional:	221 mg/m³ - Consumer: 65.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term (repeated)	
Consumer	12.5 mg/kg - Exposure: Human Oral - Frequency: Long Term (repeated)	
PNEC exposure limit values		
Styrene (100-42-5)		
Fresh Water	Value: 0.028 mg/l	
Marine water	Value: 0.028 mg/l	
Freshwater sediments	Value: 0.614 mg/kg	
Marine water sediments	Value: 0.0614 mg/kg	
Soil (agricultural)	Value: 0.2 mg/kg	
Target 14	Value: 0.04 mg/l	
Purification plant	Value: 5 mg/l	
Xylene (1330-20-7)		
Purification plant	Value: 6.58 mg/l	
Marine water	Value: 0.32 mg/l	
Intermittent emissions	Value: 0.32 mg/l	
Freshwater sediments	Value: 12.46 mg/kg	

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Styreen (100-42-5)	
Marine water sediments	Value: 12.46 mg/kg
Soil - Value	2.31 mg/kg
Fresh Water	Value: 0.32 mg/l
Biological Exposure Index	
Styrene (100-42-5)	
Value: 400 mg/g creatinine - medium: Urine - Biological Indicator: Mandelic acid in urine and fenilgliossilico - Sampling Period: End of turn	
Value: 40 mg/l creatinine - medium: Urine - Biological Indicator: Styrene in urine - Sampling Period: End of turn	
Xylene (1330-20-7)	
Value: 1.5 g/g - medium: Urine - Biological Indicator: Creatinine in urine - Sampling Period: end of turn	

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Take off immediately all contaminated clothing.

Skin and body protection	
Type	Standard
	EN 14605

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Nitrile rubber gloves		3 (> 60 minutes)	0.4		EN ISO 374

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing

Other skin protection Materials for protective clothing		
Condition	Material	Standard
	Rubber, Viton, Polyvinylchloride (PVC), Cotton dust	EN 14605

8.2.2.3. Respiratory protection

Respiratory protection:

Suitable respiratory protective device recommended

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.2.4. Thermal hazards

Thermal hazard protection:

None to our knowledge.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Ensure adequate ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: No data available
Colour	: Grey. Thixotropic paste.
Odour	: styrene.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 145 °C rif. styreen
Flash point	: 32 °C
Auto-ignition temperature	: 490 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 6.7 hPa rif. styreen (20°C)
Relative vapour density at 20 °C	: No data available
Relative density	: 1000 g/cm³
Density	: 3.6
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: > 20.5 mm²/s 40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 1.1 vol %
Upper explosive limit (UEL)	: 8 vol %

9.2. Other information

VOC content	: 174.75 g/l
-------------	--------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Oxidant. Strongly supports combustion. May react violently with combustible materials. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid the build-up of electrostatic charge. Prevent the build-up of electrostatic charge. Stable under normal conditions.

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.5. Incompatible materials

Oxidizing agent. Flammability.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological information of the main substances found in the product

Styrene (100-42-5)

Acute toxicity

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50	Rat = 11.8 mg/l - Duration: 4h
Dermal	LD50	Rat > 2000 mg/kg - Notes: OECD 402

STOT-repeated exposure

Oral	LOAEL(C)	Rat = 2000 mg/kg - Notes: bw/day
Oral	LOAEL(C)	Rat = 1000 mg/kg - Notes: bw/day
Inhalation	LOAEL(C)	Rat = 0.21 mg/l

Xylene (1330-20-7)

Acute toxicity

Oral	LD50	5627 mg/kg
Dermal	LD50	> 5000 mg/kg
Inhalative	LD50	6700 ppm - Duration: 4h

maleic anhydride (108-31-6)

Acute toxicity

Oral	LD50	1090 mg/kg bw
Dermal	LD50	2620 mg/kg (rabbit)
Inhalative	LD50	Rat = 4.35 mg/l - Duration: 1h

Styrene (100-42-5)

Acute inhalation toxicity at 1000 ppm affects the central nervous system with headaches, dizziness and coordination difficulties; irritation of the mucous membranes of the eyes and respiratory tract occurs at 500 ppm. Chronic exposure gives system depression central and peripheral nervous system with memory loss, headaches and somnolence starting from 20 ppm; digestive disorders with nausea e loss of appetite; respiratory tract irritation with chronic bronchitis; dermatosis. Repeated exposure, to low doses of the substance by inhalation, it causes irreversible changes in hearing function and can cause changes in color vision. Repeated skin exposures cause irritation. The substance degrades the skin, which can cause dryness and cracking.

Xylene (1330-20-7)

Inhalation: Harmful if inhaled. Very high concentrations of xylene lead to the progressive inhibition of the central nervous system (CNS), followed by coma, respiratory weakness, and finally absence of cerebral blood flow and death. High concentrations cause coma and respiratory weakening, destabilize the function of the kidneys and lead to liver damage. At low concentrations, irritation of the eyes, nasopharynx, illness, irritation, slow reaction times and reduced short-term memory occur. Vapors of xylene can cause dizziness, headache, nausea, mental confusion. Ingestion: In the event of ingestion of xylene, the injured person has a burning sensation and stomach ache, in case of aspiration there is a danger of chemical pneumonitis and pulmonary edema. Skin Contact: May be harmful if absorbed through the skin. Causes skin irritation. Contact with eyes: Vapors of xylene and xylene in liquid form irritate the eyes and membranes

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- i) STOT-repeated exposure;
j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Toxicological information of the main substances found in the product

Styrene (100-42-5)

Aquatic acute toxicity

LC50	Fish = 4.02 mg/l - Duration h: 96
EC50	Algae = 4.9 mg/l - Duration h: 72
EC50	Daphnia = 4.7 mg/kg - Duration h: 48
EC10	Algae = 0.28 mg/l - Duration h: 96

Aquatic chronic toxicity:

NOEC	Daphnia = 1.01 mg/l	Duration h: 504
------	---------------------	-----------------

Xylene (1330-20-7)

Acute toxicity

Endpoint	Species	Duration
EC50	Daphnia = 1 mg/l	24h
EC50	Algae = 4.36 mg/l	73h
LC50	Fish = 2.6 mg/l	96h
NOEC	Algae = 0.44 mg/l	73h
NOEC	Daphnia = 1.57 mg/l	504h
NOEC	Fish = 1.3 mg/l	1344h

maleic anhydride (108-31-6)

Acute toxicity

Endpoint	Species	Duration
LC50	Fish = 75 mg/l	96h
EC50	Daphnia = 42,81 mg/l	48h
EC50	Algae = 74,35 mg/l	72 h

Aquatic chronic toxicity

Endpoint	Species	Duration
NOEC	Daphnia = 10 mg/l	504h

12.2. Persistence and degradability

Polyester putty 3kg + hardener - extra light

Persistence and degradability	Not rapidly degradable.
-------------------------------	-------------------------

12.3. Bioaccumulative potential

Polyester putty 3kg + hardener - extra light

Bioaccumulative potential	not bioaccumulable.
---------------------------	---------------------

12.4. Mobility in soil

Polyester putty 3kg + hardener - extra light

Additional information	Avoid sub-soil penetration. Do not allow material to contaminate ground water system
------------------------	--

12.5. Results of PBT and vPvB assessment

No additional information available

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.6. Other adverse effects

No additional information available




SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number			
UN 1263	UN 1263	Not applicable	Not applicable
14.2. UN proper shipping name			
POLYESTER RESIN KIT	PAINT	Polyester resin kit	Not applicable
Transport document description			
UN 1263 POLYESTER RESIN KIT, 3, III, (E)	UN 1263 PAINT, 3, III	Not applicable	Not applicable
14.3. Transport hazard class(es)			
3	3	3	Not applicable
			Not applicable
14.4. Packing group			
III	III	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Not applicable
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F3
Special provisions (ADR) : 236, 340
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P302, R001
Transport category (ADR) : 3
Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : E

Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y370
PCA limited quantity max net quantity (IATA)	: 1kg
PCA packing instructions (IATA)	: 370
PCA max net quantity (IATA)	: 5kg
CAO packing instructions (IATA)	: 370
CAO max net quantity (IATA)	: 5kg
Special provisions (IATA)	: A66, A163
ERG code (IATA)	: 3L

Inland waterway transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : 174.75 g/l

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

Polyester putty 3kg + hardener - extra light

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
H224	Extremely flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.