

TECHNICAL SHEET

MHW 05 - Finixa machine/handwax 0.5kg

Physical properties

Physical state	Paste
Colour	white
Odour	fruity
Initial boiling point and boiling range	78
Flash point	36°C
Ignition temperature in °C	>200
VOC-value (in g/L):	35,904 % (323,134 g/l)

Analytic dates

pH	7,8	
Viscosity	5000-8000 mPa s	
Density	0,90 g/cm³	
Technical data		
Cutting power	1 - Microfine	
Gloss level	5 - Brilliant	
Protection level	6 - Extreme	
Sand paper	P5000	
Clear coat system	Conventional paintwork	Yes
	Scratch-resistant paintwork	Yes
Paint finish application	Used paintwork	Yes
	Fresh paintwork	Yes
Application	By hand	Yes
	By machine	Yes
Speed polisher	Rot. 1500 - 2000 RPM	
	Ex. 2000 - 10000 RPM	

Durability and storage conditions

Use by	732 Days
Storage temperature	15°C - 25°C

Application

Protect your paint or polished work for a long time; use this MHW 05 wax by hand or machine, by hand: rub in with POL 33, wait a few minutes and polish the excessive dry product away with a clean microfiber; used with the machine: apply at medium speed and a soft pad the product onto the panel and afterwards wipe away the excessive with a microfiber, grapefruit smell.

Shelf life

2 years

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.