

MST 819-850 – MASKING TAPE 100°C

Description

Very thin and flexible high-quality-masking-tape, developed especially for difficult surfaces, UV-resistant, single side coated with a high-temperature resistant acrylic adhesive.

Product data

Carrier	special paper
Total thickness mm	0,08
Adhesive-base	acrylic
Peel adhesion N/cm	4.8N/25mm
Tensile strength N/cm	33
Elongation %	4%
Temperature-resistance 1h/°C	up to 100
UV-resistance	up to 6 months
Weather-resistance	good
Colour	gold-yellow

Application

Masking application for oven cycles and masking in automotive paint operations.

- masking on every kind of automotive base: metal, glass, synthetic material and rubber
- never leaves glue remainders, not even after making the tape wet (for instance when degreasing) followed by infrared or oven-drying
- can also be used as fine line tape

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature 23°C, out of direct sunlight, 55% relative humidity. Stored under these conditions shelf life will be 2 years.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.