

1

SANDING

- 1** *Dry sanding*
SAND WITH FINISHING FILM DISCS
To remove paint defects

Choose your disc

Ø150mm



SFDE

Ø75mm



SFDF

+ interface pad 5mm SAM 37M

Choose your grit

P1500 or P2000

2

SANDING

- 2** *Wet sanding*
SAND WITH FOAM DISCS
To prepare the surface for polishing


Choose your disc

Ø150mm



SPDQ

Ø75mm



SPDR

Use with

P3000 + H₂O

or

water-based degreaser

1

POLISHING

- 1** **CHOOSE YOUR POLISHING PAD**



Lambswool pad

POP 108-114-117



Red foam pad
1-step

POP 308-314-317



White foam pad
Closed-cell

POP 508-514-517



Orange foam pad
Open-cell

POP 708-714-717



Black foam pad
Finish

POP 908-914-917

Cutting



After a few minutes:
heat softens the pad

Gloss



Application

Cutting &
large surfaces

Cutting with high
gloss finish,
ideal for smaller
areas

Universal pad,
ideal for smaller
areas

Universal pad,
ideal for larger
areas

To get a high
gloss and remove
holograms

- 2** Place the pad in the middle of the polisher

- 3** Apply 1-step polish paste

POL 10



- 4** Start polishing at 700 RPM

5

When the product turns transparent

SWITCH TO 1000 RPM

2

POLISHING

- 6** **FINAL PHASE**

Use the finish pad with the remaining product on the surface



Black foam pad
POP 908-914-917

Place the pad **eccentric** on the polisher & start polishing at **1000 RPM** to remove holograms

- 7** **WIPE OFF WITH MICROFIBER CLOTH**



POL 40

BONUS ROUND

BONUS ROUND

OPTIONAL

- 1** *Cleaning & waxing*
REDUCE DUST AND POLISH RESIDUE WITH SPRAY WAX

1

Spray the **Spray wax** on the surface

SPW 05



2

Wipe off with **microfiber cloth**



POL 40

3

Wipe off with another clean **microfiber cloth**



POL 40

- 2** *Add extra protection & gloss*
FINISH OFF WITH WAX

1

Place the black foam pad **eccentric** on the polisher

2

Apply **Machine & handwax**

MHW 05



3

Wipe off with **microfiber cloth**



POL 40

FINISH