



TDS

TECHNICAL DATA SHEET

TECHNICAL SHEET

SBR 10 – Finixa scuff rolls A/extra fine - red - 115mm x 10m

SBR 20 – Finixa scuff rolls S/ultra fine - grey - 115mm x 10m

SBR 30 – Finixa scuff rolls micro fine - gold - 115mm x 10m

PRODUCT SPECIFICATION

GRAIN:	SBR 10: Aluminium oxide, SBR 20 and SBR 30: silicon carbide
BONDING:	Resin over resin
BACKING:	Polyamide fibres
COLOUR:	SBR 10: Red, SBR 20: Grey and SBR 30: Gold
GRIT RANGE:	SBR 10: P360, SBR 20: P1500, SBR 30: P2000
JUMBO WIDTH:	1460 mm
MAX. NET WIDTH:	1420 mm

SBR is specially designed for sanding surfaces prior to applications of finishing coat, primer or lacquer. The product is ideal for both wet and dry sanding applications. Due to the three-dimensional structure and the high flexibility SBR is easy to use on contoured surfaces and profiles. SBR is used on painted surfaces, but also on wood, plastics and metal surfaces.

THE ABOVE PRODUCT WILL BE MANUFACTURED AND TESTED IN ACCORDANCE WITH OUR ISO9001:2008 PROCEDURES.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the product's suitability for their own applications.