

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : Finixa primer white 400ml
 UFI : 77C7-9h67-AP9N-YV7R
 Product code : TSP 140

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use
 Use of the substance/mixture : Non industrial spraying
 Industrial spraying

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor

Chemicar Europe NV
 Baarbeek 2
 2070 Zwijndrecht
 T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemicar.eu

1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
 Serious eye damage/eye irritation, Category 2 H319
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
 Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients

butanone
 Acetone
 n-butyl acetate
 2-methoxy-1-methylethyl acetate

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.
 H229 - Pressurised container: May burst if heated.
 H319 - Causes serious eye irritation.
 H336 - May cause drowsiness or dizziness.
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P501 - Dispose of contents/container to hazardous or special waste collection point, in

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

accordance with local, regional, national and/or international regulation.
P403 - Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F, 50 °C.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, eye protection.
P211 - Do not spray on an open flame or other ignition source.
P260 - Do not breathe spray.
P251 - Do not pierce or burn, even after use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.
EUH208 - Contains Fatty acids, C18-unsatd, trimers, compds. with oleylamine(Fatty acids, C18-unsatd, trimers, compds. with oleylamine). May produce an allergic reaction.

Scandinavian countries regulation

Denmark

MAL code : 4-3

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8	25 - 50	Flam. Gas 1, H220 Press. Gas
butanone; ethyl methyl ketone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1	2.5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
trizinc bis(orthophosphate)	(CAS-No.) 7779-90-0 (EC-No.) 231-944-3 (EC Index-No.) 030-011-00-6	2.5 - 10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-methoxy-1-methylethyl acetate	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7	1 - 2.5	Flam. Liq. 3, H226
Fatty acids, C18-unsatd., trimers, compds. with oleylamine	(CAS-No.) 147900-93-4	0.1 - 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact : No irritant effect.
First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Get medical advice/attention if you feel unwell.
First-aid measures after ingestion : Do not induce vomiting. Immediately call a POISON CENTER/doctor.

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO₂). extinguishing powder. Water fog. Alcohol resistant foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting : Approved respirator.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing. Evacuate area.

6.1.1. For non-emergency personnel

Emergency procedures : Keep public away.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow product to spread into the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Provide adequate ventilation. Take up liquid spill into inert absorbent material.
Methods for cleaning up : Do not flush with water.

6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Handle and open container with care. Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Store in dry, cool, well-ventilated area. Protect from heat and direct sunlight. Container should not be closed gas-tight.

Special rules on packaging : Container should not be closed gas-tight. Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dimethyl ether (115-10-6)		
EU	Local name	Dimethylether
EU	IOELV TWA (mg/m ³)	1920 mg/m ³
EU	IOELV TWA (ppm)	1000 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Oxyde de diméthyle # Dimethylether
Belgium	Limit value (mg/m ³)	1920 mg/m ³
Belgium	Limit value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
acetone; propan-2-one; propanone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m ³)	1210 mg/m ³

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

acetone; propan-2-one; propanone (67-64-1)		
EU	IOELV TWA (ppm)	500 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Acétone # Aceton
Belgium	Limit value (mg/m ³)	1210 mg/m ³
Belgium	Limit value (ppm)	500 ppm
Belgium	Short time value (mg/m ³)	2420 mg/m ³
Belgium	Short time value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
78-93-3 butanone		
WEL	Short-term value:	899 mg/m ³ , 300 ppm
	Long-term value	600 mg/m ³ , 200 ppm
	Sk, BMGV	
67-64-1 Acetone		
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm	
123-86-4 n-butyl acetate		
WEL	Short-term value:	966 mg/m ³ , 200 ppm
	Long-term value	724 mg/m ³ , 150 ppm
108-65-6 2-methoxy-1-methylethyl acetate		
WEL	Short-term value Long-term value Sk	548 mg/m ³ , 100 ppm 274 mg/m ³ , 50 ppm
DNELs		
78-93-3 butanone		
Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
		1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m ³ (Consumer)
		600 mg/m ³ (Worker)
67-64-1 Acetone		
Oral	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
		186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	2420 mg/m ³ (Worker)
	DNEL Long term-systemic	200 mg/m ³ (Consumer)
		1210 mg/m ³ (Worker)
123-86-4 n-butyl acetate		
Inhalative	DNEL Acute-systemic	859.7 mg/m ³ (Consumer)
		960 mg/m ³ (Worker)
	DNEL Acute-local	859.7 mg/m ³ (Consumer)
		960 mg/m ³ (Worker)
	DNEL Long term-systemic	102.34 mg/m ³ (Consumer)
		480 mg/m ³ (Worker)
	DNEL Long term-local	102.34 mg/m ³ (Consumer)
		480 mg/m ³ (Worker)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	DNEL Long term-systemic	1.67 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	54.8 mg/kg bw/day (Consumer)
		153.5 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	33 mg/m ³ (Consumer)
		275 mg/m ³ (Worker)

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNECs	
acetone; propan-2-one; propanone (67-64-1)	
PNEC Marine water	1.06 mg/l (Undefined)
PNEC Freshwater sediment	30.4 mg/l(dry weight) (Undefined)
PNEC Soil	29.5 (Undefined)
PNEC Marine water sediment	3.04 mg/l(dry weight) (Undefined)
123-86-4 n-butyl acetate	
PNEC Freshwater	0.18 mg/l (Undefined)
PNEC Marine water	0.015 mg/l (Undefined)
PNEC Freshwater sediment	0.981 mg/l(dry weight) (Undefined)
PNEC Intermittent release	0.36 (Undefined)
PNEC Soil	0.0903 (Undefined)
PNEC Sewage Treatment Plant	35.6 mg/l (Undefined)
PNEC Marine water sediment	0.0981 mg/l(dry weight) (Undefined)
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC Freshwater	0.635 mg/l (Undefined)
PNEC Marine water	0.0635 mg/l (Undefined)
PNEC Freshwater sediment	3.29 mg/l(dry weight) (Undefined)
PNEC Intermittent release	6.35 (Undefined)
PNEC Soil	0.29 (Undefined)
PNEC Sewage Treatment Plant	100 mg/l (Undefined)
PNEC Marine water sediment	0.329 mg/l(dry weight) (Undefined)
Ingredients with biological limit values	
78-93-3 butanone	
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

8.2. Exposure controls

Appropriate engineering controls:

Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Wash hands before breaks and after work. Do not breathe gas/vapour/aerosol. Avoid contact with skin and eyes.

Hand protection:

Wear gloves according to EN374 resistant to the solvent(s) in use. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Nitrile rubber gloves	Nitrile rubber (NBR)	5 (> 240 minutes), 6 (> 480 minutes)	>0.5		EN 374

Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Safety glasses			EN 166

Skin and body protection:

Wear suitable protective clothing

Type	Standard
	EN 13034

Respiratory protection:

Device	Filter type	Condition	Standard
Gas filters	Filter AX (brown)	Short term exposure	
Self-contained breathing apparatus (SCBA)	Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust	Long term exposure	

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Colour	: white.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 55.8 - 56.6 °C
Flash point	: -42 °C
Auto-ignition temperature	: 235 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 5200 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.888 g/cm ³
Solubility	: Practically not miscible.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 1.5 vol %
Upper explosive limit (UEL)	: 18.6 vol %

9.2. Other information

VOC content	: 663.4 g/l
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
-----------------------	------------------

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

LD/LC50 values relevant for classification		
78-93-3 butanone		
Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
		5000 mg/kg (rbt)
67-64-1 Acetone		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	7800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)
123-86-4 n-butyl acetate		
Oral	LD50	10760 mg/kg (rat)
Dermal	LD50	>14000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)
7779-90-0 trizinc bis(orthophosphate)		
Oral	LD50	5000 mg/kg (rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Aquatic toxicity		
78-93-3 butanone		
LC50/96h	2993 mg/l (Pimephales promelas)	
EC50/48h	308 mg/l (Daphnia magna)	
67-64-1 Acetone		
EC50	8800 mg/l (Daphnia magna)	
	8300 mg/l (Fish)	
123-86-4 n-butyl acetate		
LC50/96h	18 mg/l (Fish)	
EC50/48h	44 mg/l (Daphnia magna)	
7779-90-0 trizinc bis(orthophosphate)		
LC50/96h	0.14 mg/l (Oncorhynchus mykiss (96h))	
EC50/48h	2.34 mg/l (Daphnia magna)	
ErC(50) (72h)	0.14 mg/l (Desmodesmus subspicatus)	

12.2. Persistence and degradability

Finixa primer white 400ml	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

No additional information available

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations. Do not dispose of with domestic waste. Do not discharge into drains.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number			
1950	1950	1950	1950
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
UN 1950 , 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 , 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 , 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 , 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available			

14.6. Special precautions for user

- Overland transport

Transport regulations (ADR) : Subject to the provisions
Classification code (ADR) : 5F
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0
Tunnel restriction code (ADR) : D

- Transport by sea

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E0
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

- Air transport

No data available

- Inland waterway transport

Classification code (ADN) : 5F

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	butanone; ethyl methyl ketone - acetone; propan-2-one; propanone
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	butanone; ethyl methyl ketone - acetone; propan-2-one; propanone
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	butanone; ethyl methyl ketone - acetone; propan-2-one; propanone
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	dimethyl ether - butanone; ethyl methyl ketone - acetone; propan-2-one; propanone

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 663.4 g/l

VOC-CH : 74.70%

15.1.2. National regulations

Class	Share in %
NK	50-<75

Germany

Reference to AwSV : Water hazard class (WGK) 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

Waterbevaarlijkheid : 6 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

SZW-lijst van kankerverwekkende stoffen : 2-methoxy-1-methylethyl acetate, Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] are listed

SZW-lijst van mutagene stoffen : Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Finixa primer white 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Fatty acids, C18-unsatd, trimers, compds. with oleylamine(Fatty acids, C18-unsatd, trimers, compds. with oleylamine). May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.