

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Trade name	: Finixa 1K Clear coat - 400ml
Product code	: TSP 180
Product group	: Blend

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use, Consumer use
Industrial/Professional use spec	: Cleaner
Use of the substance/mixture	: Coatings and paints, thinners, paint removers Cleaner
Function or use category	: Non industrial spraying, Industrial spraying

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Chemicar Europe NV  
 Baarbeek 2  
 2070 Zwijndrecht  
 T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89  
[info@chemicar.eu](mailto:info@chemicar.eu)

#### 1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Full text of H statements : see section 16	


##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP)	: Danger
Hazardous ingredients	: acetone; propan-2-one; propanone; n-butyl acetate; 1-methoxy-2-propanol; monopropylene glycol methyl ether; ethyl acetate
Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use.

# Finixa 1K Clear coat - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P260 - Do not breathe spray.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves, eye protection.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403 - Store in a well-ventilated place.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

### Scandinavian countries regulation

#### Denmark

MAL code : 4-3

#### 2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8	25 - 50	Flam. Gas 1, H220 Press. Gas
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1	25 - 50	Flam. Liq. 3, H226 STOT SE 3, H336
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
1-methoxy-2-propanol; monopropylene glycol methyl ether	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3	2.5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
ethyl acetate	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5	2.5 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-butoxyethyl acetate; butylglycol acetate	(CAS-No.) 112-07-2 (EC-No.) 203-933-3 (EC Index-No.) 607-038-00-2	2.5 - 10	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Assure fresh air breathing. If you feel unwell, seek medical advice.  
First-aid measures after skin contact : No irritant effect.  
First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open.  
First-aid measures after ingestion : Do NOT induce vomiting. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water fog. extinguishing powder. carbon dioxide (CO2). Alcohol resistant foam.  
Unsuitable extinguishing media : Do not use a heavy water stream.

# Finixa 1K Clear coat - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Protection during firefighting : [In case of inadequate ventilation] wear respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Warn road users and passers by to keep away from danger area.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Other information : Do not flush with water. Ensure there is adequate ventilation.

### 6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Do not pierce or burn, even after use. Take precautionary measures against static discharge. Handle and open container with care. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store in a dry place. Store in a closed container. Protect from sunlight. Store in a well-ventilated place.

Storage area : Store away from heat. Store in a well-ventilated place.

Special rules on packaging : Store in a closed container. Container should not be closed gas-tight.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

dimethyl ether (115-10-6)		
EU	Local name	Dimethylether
EU	IOELV TWA (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	1000 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Oxyde de diméthyle # Dimethylether
Belgium	Limit value (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
acetone; propan-2-one; propanone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	500 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Acétone # Aceton
Belgium	Limit value (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	500 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	1000 ppm

# Finixa 1K Clear coat - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>acetone; propan-2-one; propanone (67-64-1)</b>		
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
<b>n-butyl acetate (123-86-4)</b>		
WEL	Short-term value	966 mg/m <sup>3</sup> , 200 ppm
	Long-term value	724 mg/m <sup>3</sup> , 150 ppm
<b>1-methoxy-2-propanol (107-98-2)</b>		
WEL	Short-term value	560 mg/m <sup>3</sup> , 150 ppm
	Long-term value	375 mg/m <sup>3</sup> , 100 ppm
	Sk	
<b>ethyl acetate (141-78-6)</b>		
WEL	Short-term value	400 ppm
	Long-term value	200 ppm
<b>2-butoxyethyl acetate (112-07-2)</b>		
WEL	Short-term value	332 mg/m <sup>3</sup> , 50 ppm
	Long-term value	133 mg/m <sup>3</sup> , 20 ppm
	Sk	
<b>DNELs</b>		
<b>acetone; propan-2-one; propanone (67-64-1)</b>		
Oral	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
		186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	2,420 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	200 mg/m <sup>3</sup> (Consumer)
		1,210 mg/m <sup>3</sup> (Worker)
<b>ethyl acetate (141-78-6)</b>		
Oral	DNEL Long term-systemic	4.5 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	37 mg/kg bw/day (Consumer)
		63 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-systemic	734 mg/m <sup>3</sup> (Consumer)
		1,468 mg/m <sup>3</sup> (Worker)
	DNEL Acute-local	734 mg/m <sup>3</sup> (Consumer)
		1,468 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	367 mg/m <sup>3</sup> (Consumer)
		34 mg/m <sup>3</sup> (Worker)
	DNEL Long term-local	367 mg/m <sup>3</sup> (Consumer)
		734 mg/m <sup>3</sup> (Worker)
<b>PNECs</b>		
<b>acetone; propan-2-one; propanone (67-64-1)</b>		
PNEC Marine water	1.06 (Undefined)	
PNEC Freshwater sediment	30.4 (Undefined)	
PNEC Soil	29.5 (Undefined)	
PNEC Marine water sediment	3.04 (Undefined)	
<b>ethyl acetate (141-78-6)</b>		
PNEC Freshwater	0.26 (Undefined)	
PNEC Marine water	0.026 (Undefined)	
PNEC Freshwater sediment	0.34 (Undefined)	
PNEC Soil	0.22 (Undefined)	
PNEC Sewage Treatment Plant	650 (Undefined)	
PNEC Marine water sediment	0.034 (Undefined)	

## 8.2. Exposure controls

### Appropriate engineering controls:

Always wash your hands immediately after handling this product, and once again before leaving the workplace.

### Hand protection:

Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

# Finixa 1K Clear coat - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	5 (> 240 minutes), 6 (> 480 minutes)	> 0.5		EN 374

### Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
			EN 166

### Skin and body protection:

Wear suitable protective clothing

Type	Standard
	EN 13034

### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Device	Filter type	Condition	Standard
	Type P2	In the event of insufficient ventilation:	
Self-contained breathing apparatus (SCBA)	Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust	Long term exposure	

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: 0 °C
Freezing point	: No data available
Boiling point	: 55.8 - 56.6 °C
Flash point	: -97 °C
Auto-ignition temperature	: 235 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 4 bar
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.79 g/cm <sup>3</sup> (20°C)
Solubility	: Moderately soluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 1.7 vol %
Upper explosive limit (UEL)	: 20 vol %

# Finixa 1K Clear coat - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 9.2. Other information

VOC content : 710.5 g/l VOC-CH: 90.15%

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

acetone; propan-2-one; propanone (67-64-1)		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	7,800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)
ethyl acetate (141-78-6)		
Oral	LD50	4,100 mg/kg (mouse)
Dermal	LC50/4h	1,580 mg/kg (rbt)

Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified  
Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : No data available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Acute aquatic toxicity : Not classified

acetone; propan-2-one; propanone (67-64-1)	
EC50	8,800 mg/l (Daphnia magna)
	8,300 mg/l (Fish)
ethyl acetate (141-78-6)	
EC50/48h	0,164 mg/l (Daphnia magna)
	3.3 mg/l (Scenedesmus subspicatus)
EC50	7.4 mg/l (pseudomonas fluorescens)

Chronic aquatic toxicity : Not classified

# Finixa 1K Clear coat - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### Finixa 1K Clear coat - 400ml

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

### 12.6. Other adverse effects

No additional information available




## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Do not dispose of with domestic waste.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations. Discharging into rivers and drains is forbidden.

## SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
<b>14.1. UN number</b>		
1950	1950	1950
<b>14.2. UN proper shipping name</b>		
AEROSOLS	AEROSOLS	Aerosols, flammable
<b>Transport document description</b>		
UN 1950 AEROSOLS (), 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 11  
Excepted quantities (ADR) : E0  
Packing instructions (ADR) : P207  
Special packing provisions (ADR) : PP87, RR6, L2  
Mixed packing provisions (ADR) : MP9  
Transport category (ADR) : 2  
Special provisions for carriage - Packages (ADR) : V14  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12

# Finixa 1K Clear coat - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special provisions for carriage - Operation (ADR) : S2

Tunnel restriction code (ADR) : D

### - Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP02

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

### - Air transport

PCA Excepted quantities (IATA) : E0

PCA Limited quantities (IATA) : Y203

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 203

PCA max net quantity (IATA) : 75kg

CAO packing instructions (IATA) : 203

CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 710.5 g/l:

VOC-CH 90.15%

#### 15.1.2. National regulations

Class	Share in %
NK	75-<100

#### Germany

Reference to AwSV : Water hazard class (WGK) 1, low hazard to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

#### Netherlands

Waterbezwaarlijkheid : 11 - Weinig schadelijk voor in het water levende organismen

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

#### Denmark



# Finixa 1K Clear coat - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
PBT	Persistent Bioaccumulative Toxic

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas	Gases under pressure
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*