

TECHNICAL SHEET

TSP 310 – Finixa sanding guide black 400ml

APPLICATION

Dry Guide Coat is a very quick drying laquerspray based on an acrylic resin. This product is used for surface control after repairing a car carrosserie damage.

Yield	:	400 ml, for 1-2 m ²
Number of layers	:	Dependent on the filmthickness: 1 layer
Application	:	Free surface of rust, dirt; let it dry. Cover the parts which should not to be painted. Shake the aerosol well before use during 2 to 3 minutes. Spray several thin layers from a distance of appr. 30 cm. Turn the aerosol up side down after use and spray till only gas is coming out.
Over paintable	:	After 10 minutes. After 15 minutes tack-free. Dry within 30 minutes.

TECHNICAL INFORMATION

Resin	:	Acrylic resin
Pigments	:	lead free
Solvents	:	white spirit/Xylen
PVC	:	7 V/V %
Solids	:	±21 %(m/m)
Recommended film-thickness / layer	:	± 40 micron wet, 10 – 15 micron dry.
Gloss	:	matt
Density	:	± 0.711 kg/l
Particle size	:	5-15 micron
Colour	:	Black
Thinner	:	DMK, IPA

The above information is given in good faith, but the user should assure himself that the performance of the product is

sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the product suitability for their own applications.