

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| | |
|---------------|---------------------------|
| Product form | : Mixture |
| Trade name | : Structure spray - 400ml |
| UFI | : 98D7-CHG0-0P9K-WY7H |
| Product code | : TSP 550 |
| Vaporizer | : Aerosol |
| Product group | : Aerosols |

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

| | |
|----------------------------------|---|
| Industrial/Professional use spec | : Industrial For professional use only |
| Function or use category | : Coating solution |

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Chemicar Europe NV
Baarbeek, 2
2070 Zwijndrecht
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemicar.eu

1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

| | |
|--|-----------|
| Aerosol, Category 1 | H222;H229 |
| Skin corrosion/irritation, Category 2 | H315 |
| Serious eye damage/eye irritation, Category 2 | H319 |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336 |
| Specific target organ toxicity – Repeated exposure, Category 2 | H373 |
| Hazardous to the aquatic environment – Chronic Hazard, Category 3 | H412 |
| Full text of H- and EUH-statements: see section 16 | |

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Danger

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|--------------------------------|--|
| Contains | : acetone; propan-2-one; propanone, Reaction mass of ethylbenzene and xylene, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, butanone; ethyl methyl ketone, Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine |
| Hazard statements (CLP) | : H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H317 - May cause an allergic skin reaction. H336 - May cause drowsiness or dizziness. H373 - May cause damage to organs through prolonged or repeated exposure. H412 - Harmful to aquatic life with long lasting effects. |
| Precautionary statements (CLP) | : P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves, eye protection, face protection. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P311 - IF exposed or concerned: Call a POISON CENTER or doctor. P312 - Call a POISON CENTRE or doctor if you feel unwell. P403 - Store in a well-ventilated place. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. |

Nordic countries regulation

Denmark

MAL code : 5-3

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Aerosol propellant.

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|----------------|--|---------|---|
| dimethyl ether | CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 | 25 – 50 | Flam. Gas 1A, H220 Press. Gas |

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|----------|--|
| Reaction mass of ethylbenzene and xylene | EC-No.: 905-588-0 | 10 – 25 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |
| acetone; propan-2-one; propanone | CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 | 2.5 – 10 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics | CAS-No.: 68920-06-9 EC-No.: 920-750-0 | 2.5 – 10 | Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |
| n-butyl acetate | CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 | 2.5 – 10 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| butanone; ethyl methyl ketone | CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 | 2.5 – 10 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| 1-methoxy-2-propanol; monopropylene glycol methyl ether | CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 | 0.1 – 1 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| HYDROGENATED TALLOWALKONIUM CHLORIDE | CAS-No.: 61789-72-8 EC-No.: 263-081-3 | 0.25 – 1 | Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 |
| Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine | CAS-No.: 162627-17-0 EC-No.: 605-296-0 REACH-no: 01-2119970640-38 | 0.1 – 1 | Flam. Liq. 3, H226 STOT SE 3, H336 |

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures after inhalation | : Allow affected person to breathe fresh air. Get medical advice/attention if you feel unwell. |
| First-aid measures after skin contact | : No irritant effect. |
| First-aid measures after eye contact | : Rinse opened eye for several minutes under running water. Then consult doctor. |
| First-aid measures after ingestion | : If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. |

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water fog. extinguishing powder. carbon dioxide (CO₂). Alcohol resistant foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting : Approved respirator.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing. Keep public away.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Provide adequate ventilation. Do not flush with water.

6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool place. Take action to prevent static discharges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Storage conditions : Keep container closed when not in use. Keep container tightly closed. Protect from heat and direct sunlight.
Special rules on packaging : Store in a closed container. Container should not be closed gas-tight.

7.3. Specific end use(s)

No additional information available

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| acetone; propan-2-one; propanone (67-64-1) | |
|---|--|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Acetone |
| IOEL TWA | 1210 mg/m ³ |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| Belgium - Occupational Exposure Limits | |
| Local name | Acétone # Aceton |
| OEL TWA | 594 mg/m ³ |
| OEL TWA [ppm] | 246 ppm |
| OEL STEL | 1187 mg/m ³ |
| OEL STEL [ppm] | 492 ppm |
| Regulatory reference | Koninklijk besluit/Arrêté royal 11/05/2021 |
| dimethyl ether (115-10-6) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Dimethylether |
| IOEL TWA | 1920 mg/m ³ |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| Belgium - Occupational Exposure Limits | |
| Local name | Oxyde de diméthyle # Dimethylether |
| OEL TWA | 1920 mg/m ³ |
| OEL TWA [ppm] | 1000 ppm |
| Regulatory reference | Koninklijk besluit/Arrêté royal 11/05/2021 |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Always wash your hands immediately after handling this product, and once again before leaving the workplace. Do not breathe gas.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Protective goggles

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Eye protection | | | |
|----------------|----------------------|-----------------|----------|
| Type | Field of application | Characteristics | Standard |
| | | | EN 166 |

8.2.2.2. Skin protection

Hand protection:

Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use

| Hand protection | | | | | |
|-----------------|----------------------|--------------------------------------|----------------|-------------|------------|
| Type | Material | Permeation | Thickness (mm) | Penetration | Standard |
| | Nitrile rubber (NBR) | 5 (> 240 minutes), 6 (> 480 minutes) | 0.5 | | EN ISO 374 |

8.2.2.3. Respiratory protection

| Respiratory protection | | | |
|------------------------|-----------------------|-----------|----------|
| Device | Filter type | Condition | Standard |
| | Type P2, Filter A2/B2 | | |

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | : Gas |
| Colour | : Black. |
| Odour | : characteristic. |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : -24.8 °C (115-10-6 Dimethylether) |
| Flash point | : -42 °C |
| Auto-ignition temperature | : > 200 °C |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : 5200 hPa |
| Relative vapour density at 20°C | : No data available |
| Relative density | : No data available |
| Density | : 0.843 g/m ³ |
| Solubility | : Moderately soluble in water. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Viscosity, kinematic | : ≤ 20.5 mm ² /s 40 °C (L)c |
| Viscosity, dynamic | : 7500 – 10500 Brookfield sp3 6 rpm |
| Explosive properties | : In use, may form flammable/explosive vapour-air mixture. |
| Oxidising properties | : No data available |
| Lower explosive limit (LEL) | : 0.7 vol % |
| Upper explosive limit (UEL) | : 18.6 vol % |

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

9.2. Other information

VOC content : 622.1 g/l VOC-CH 73,78%
Additional information : 25,4 % Solid content. 73.8% Organic solvents

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified
Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

acetone; propan-2-one; propanone (67-64-1)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

Reaction mass of ethylbenzene and xylene

| | |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics (68920-06-9)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

n-butyl acetate (123-86-4)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|---|--|
| butanone; ethyl methyl ketone (78-93-3) | |
| STOT-single exposure | May cause drowsiness or dizziness. |
| Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine (162627-17-0) | |
| STOT-single exposure | May cause drowsiness or dizziness. |
| STOT-repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |
| Reaction mass of ethylbenzene and xylene | |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not classified |
| Structure spray - 400ml | |
| Vaporizer | Aerosol |
| Viscosity, kinematic | ≤ 20.5 mm ² /s 40 °C (L)c |

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Do not dispose of with domestic waste. Do not discharge into drains.

Structure spray - 400ml





Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|---------|--|
| HP Code | : HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment |
|---------|--|

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

| ADR | IMDG | IATA | ADN |
|---|---|--|---|
| 14.1. UN number | | | |
| UN 1950 | UN 1950 | UN 1950 | UN 1950 |
| 14.2. UN proper shipping name | | | |
| AEROSOLS | AEROSOLS | Aerosols, flammable | AEROSOLS |
| Transport document description | | | |
| UN 1950 AEROSOLS, 2.1, (D) | UN 1950 AEROSOLS, 2.1 | UN 1950 Aerosols, flammable, 2.1 | UN 1950 AEROSOLS, 2.1 |
| 14.3. Transport hazard class(es) | | | |
| 2.1 | 2.1 | 2.1 | 2.1 |
|  |  |  |  |
| 14.4. Packing group | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | | |
| Dangerous for the environment: No | Dangerous for the environment: No Marine pollutant: No | Dangerous for the environment: No | Dangerous for the environment: No |
| No supplementary information available | | | |

14.6. Special precautions for user

Overland transport

| | |
|----------------------------------|----------------------|
| Classification code (ADR) | : 5F |
| Special provisions (ADR) | : 190, 327, 344, 625 |
| Limited quantities (ADR) | : 1I |
| Excepted quantities (ADR) | : E0 |
| Packing instructions (ADR) | : P207 |
| Special packing provisions (ADR) | : PP87, RR6, L2 |

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|---|-------------|
| Mixed packing provisions (ADR) | : MP9 |
| Transport category (ADR) | : 2 |
| Special provisions for carriage - Packages (ADR) | : V14 |
| Special provisions for carriage - Loading, unloading and handling (ADR) | : CV9, CV12 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Tunnel restriction code (ADR) | : D |

Transport by sea

| | |
|-----------------------------------|------------------------------------|
| Special provisions (IMDG) | : 63, 190, 277, 327, 344, 381, 959 |
| Packing instructions (IMDG) | : P207, LP200 |
| Special packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D |
| EmS-No. (Spillage) | : S-U |
| Stowage category (IMDG) | : None |
| Stowage and handling (IMDG) | : SW1, SW22 |
| Segregation (IMDG) | : SG69 |

Air transport

| | |
|--|--------------------|
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |

Inland waterway transport

| | |
|-----------------------------------|----------------------|
| Classification code (ADN) | : 5F |
| Special provisions (ADN) | : 190, 327, 344, 625 |
| Limited quantities (ADN) | : 1 L |
| Excepted quantities (ADN) | : E0 |
| Equipment required (ADN) | : PP, EX, A |
| Ventilation (ADN) | : VE01, VE04 |
| Number of blue cones/lights (ADN) | : 1 |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 622.1 g/l VOC-CH 73,78%

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

| Name | CAS-No. | Combined Nomenclature code (CN) | Combined Nomenclature code for mixture without constituents which would determine classification under another CN code |
|---------|---------|---------------------------------|--|
| Acetone | 67-64-1 | 2914 11 00 | ex 3824 99 92 |

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

| Name | CN designation | CAS-No. | CN code | Category | Threshold | Annex |
|-------------------|----------------|---------|------------|------------|-----------|---------|
| Acetone | | 67-64-1 | 2914 11 00 | Category 3 | | Annex I |
| Methylethylketone | Butanone | 78-93-3 | 2914 12 00 | Category 3 | | Annex I |

15.1.2. National regulations

France

| Occupational diseases | |
|-----------------------|---|
| Code | Description |
| RG 84 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

Waterbezwaarlijkheid : 1 - Black list substance
SZW-lijst van kankerverwekkende stoffen : Quartz
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – : None of the components are listed
Vruchtbaarheid
SZW-lijst van reprotoxische stoffen – Ontwikkeling : 2-methoxypropanol

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

| | |
|---------------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment – Acute Hazard, Category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment – Chronic Hazard, Category 2 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Gas 1A | Flammable gases, Category 1A |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H229 | Pressurised container: May burst if heated. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| Press. Gas | Gases under pressure |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT RE 2 | Specific target organ toxicity – Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |

Safety Data Sheet (SDS), EU

Structure spray - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.