

### TECHNICAL SHEET

### TSP 910 – Finixa spray matt black 400ml

#### Product information

TSP 910 is a lacquer that can be used on metal, wood, paper, and (primed) hard plastics. It builds up a tough film that has good adhesion. The product is based on a nitrocellulose/alkyd combination and dries very fast. The surface gets a protective layer and a completely new look. For good anti-corrosion properties on bare metals the use of a special anti-corrosion primer is recommended.

#### Application:

Free surface of rust, dirt; let it dry. Cover the parts which should not to be painted. Shake the aerosol well before use during 2 to 3 minutes. Spray several thin layers from a distance of appr. 30 cm. Turn the aerosol up side down after use and spray till only gas is coming out.

#### Technical Information:

Resin	:	Nitrocellulose/Acrylic resin combination.
Pigments	:	Lead-free
PVC	:	8 V/V %
Solids	:	± 11.6 % (m/m)
Recommended film thickness	:	± 75 micron wet, 15-20 micron dry.
Gloss – 2 layers	:	0.0 @20° - 8.0 (+-0.4) @60°
Density	:	± 0.711 kg/l
Particle size	:	5-15 micron
Colour	:	Black
Thinner	:	DMK.
Yield	:	400 ml for 1-2 m <sup>2</sup>
Coverage	:	Dependent on the film thickness: 2 to 3 layers
Over paintable	:	With the same product: After 10 minutes. Tack-free after 20 minutes Dry after 5 Hours (At 20°C, 40 Mu layer)

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the product's suitability for their own applications.*