

TDS TECHNICAL DATA SHEET

TECHNICAL SHEET TSP 920 - Finixa fade out thinner 400ml

Product information

Finixa fade out thinner is used to make a perfect transition between an existing and new sprayed clear coat. TSP 920 can be used with all A-brands clear coats.

There is no spray gun needed and ideal for a SMART repair.

Product characteristics

- Smooth transitions in the spraying zone
- No influence on dependent color
- Can dry up, then has to be polished
- Ideal for 'spot repair'

Application

Repair, apply the primer and sand.

Then apply the base and let it dry.

To create a smooth transition, the base coat should be sprayed past the primed surface.

Then the clear coat is applied.

Use the fade out thinner to prevent line formation and to obtain a nice transition between the old and new clear coat.

Finixa fade out thinner is applied in a thin sprayed layer from the new clear coat to the old one. Afterwards the transition can be polished to obtain a perfect finished result.

Shelf life and storage

Shelf life: 2 years after production

Storage: Place in a dry and well-ventilated area away from direct sunlight and freezing temperatures. Store between 5° C – 41° F and 25° C – 77° F.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the product suitability for their own applications.

T.: +32 3 234 87 80

F.: +32 3 234 87 89

info@chemicar.eu

www.chemicar.eu